
MANASSAS RGNL/HARRY P DAVIS FLD (See WASHINGTON on page 52)

RONALD REAGAN WASHINGTON NTL (See WASHINGTON on page 53)

SOUTH CAPITOL STREET HELIPORT (See WASHINGTON on page 54)

WASHINGTON**MANASSAS RGNL/HARRY P DAVIS FLD** (HEF)(KHEF) 28 WSW UTC-5(-4DT)**WASHINGTON****COPTER**H-10H, 12I, L-29E, 34E, 36I, A
IAP, AD

N38°43.26' W77°30.91'

192 B TPA—See Remarks LRA NOTAM FILE HEF

RWY 16L-34R: H6200X100 (ASPH-GRVD) S-50, D-140 HIRL**RWY 16L:** MALSR. PAPI(P4L)—GA 3.0° TCH 55'. Trees.**RWY 34R:** MALSF. PAPI(P4L)—GA 3.0° TCH 40'. Trees. Rgt tfc.**RWY 16R-34L:** H3715X75 (ASPH) S-12.5 MIRL 0.3% up N**RWY 16R:** REIL. PAPI(P2L)—GA 3.0° TCH 54'. Tree. Rgt tfc.**RWY 34L:** REIL. PAPI(P2L)—GA 3.0° TCH 43'. Trees.**SERVICE:** S4 FUEL 100LL, JET A OX 1, 2, 4 LGT When ATCT clsd

actvt MALSR Rwy 16L; MALSF Rwy 34R; REILS Rwy 16R & 34L;

HIRL Rwy 16L-34R, MIRL Rwy 16R-34L—CTAF.

NOISE: Helicopter ops over residential areas blw 1000 ft should be avoided; ctc amgr 703-361-1882 for info.**AIRPORT REMARKS:** Attended 1130-0330Z†. Birds and deer on and invof

arpt. TPA—1200(1008) single engine and light twin acct,

1500(1308) med twin and turboprop acct, 1000(808) helicopter.

Twy B safety area wid 44' laterally east side fm Twy E to Twy G. U.S.

Customs avbl Mon-Sun 1000-0400Z†. Call Command Center

703-661-2800 for appointment. 24 hr notice required. All weekend

flights must be arranged before 2200Z† on Fri before. Terminal apron

for transient and US Customs parking.

AIRPORT MANAGER: 703-361-1882**WEATHER DATA SOURCES:** AWOS-3PT (703) 361-6160**COMMUNICATIONS:** CTAF 133.1 ATIS 125.175 (703) 361-6160Ⓡ **POTOMAC APP/DEP CON** 128.525**TOWER** 133.1 (1130-0330Z†) **GND CON** 121.8**CLNC DEL** 120.2 (When twr clsd)**CLEARANCE DELIVERY PHONE:** For CD when ATCT is clsd ctc Potomac Apch at 866-709-4993.**AIRSPACE:** CLASS D svc 1130-0330Z†; other times CLASS E.**RADIO AIDS TO NAVIGATION:** NOTAM FILE IAD.**ARMEL (L) (L) VORW/DME** 113.5 AML Chan 82 N38°56.08' W77°28.00' 198° 13.0 NM to fld. 296/8W.

VOR unusable:

055°-092° blo 4,500'

093°-115°

116°-210° blo 4,500'

DME unusable:

055°-210° byd 28 NM blo 2,500'

211°-230° byd 30 NM blo 3,000'

ILS 109.1 I-HEF Rwy 16L. Class IE.