

NELLIS AFB (LSV)(KLSV) AF 7 NE UTC-8(-7DT) N36°14.17' W115°02.06'

1869 B NOTAM FILE LSV Not insp.

RWY 03L-21R: H10120X200 (CONC) PCN 21 R/B/W/T HIRL

RWY 03L: PAPI(P4L)—GA 3.0° TCH 52'. Rgt tfc.

RWY 21R: PAPI(P4L)—GA 3.0° TCH 50'. Rgt tfc.

RWY 03R-21L: H10051X150 (CONC) PCN 49 R/B/W/T HIRL

RWY 03R: ALSF1. PAPI(P4L)—GA 3.0° TCH 53'. RVR-T Rgt tfc.

RWY 21L: ALSF1. PAPI(P4L)—GA 3.0° TCH 54'. RVR-R Rgt tfc.

ARRESTING GEAR/SYSTEM

RWY 03L HOOK BAK-12B(B)(41'OVNRN) HOOK BAK-12B(B)(1211').

HOOK BAK-12B(B)(1451') HOOK BAK-12B(B)(41' OVNRN). **RWY 21R**

RWY 03R HOOK BAK-12B(B)(41' OVNRN) HOOK BAK-14 HOOK BAK-12B(B)(1226').

HOOK BAK-14 HOOK BAK-12B(B)(1200') HOOK BAK-12B(B)(46' OVNRN). **RWY 21L**

SERVICE: S4 **FUEL** JET A++ **OX** 1, 2 **LGT** Rwy thr lgts gated. Rwy 21L PAPI RRP and ILS RPI not coincidental. Rwy 03R

and 21L ALSF-1 apch lgts NTE step 3 intst. Twy edge lgts adj to main aprn prkg rows 1 and 2 misg. **MILITARY—A-GEAR** All BAK-12 extn and in raised posn, rqr 30 min PN for removal. Rwy 03R-21L BAK-14 ops: both BAK-14 apch end and dep end will be in lowered pos. Avbl upon req for emer use only. Slow to 20 kts or less prior to dep end cable and taxi to far edge of cold side of rwy; taxi btn rwy edge and outermost BAK-14 bumper. **JASU** No starter unit for F4B, F4J, no starter probe for USN acft; 2(MA-1A) **FUEL** A++ . Fuel will not be ordered til acft is prk. **FLUID** W-Exp 2-3 hr delat, SP PRESAIR LHOX LOX. **OIL** O-123-128-132-133-148-156 SOAP **TRAN ALERT** Avbl Mon-Fri 1600Z-0400Z, no quick turn Fri-Sun. No tsnt acft can arr/dep durg ACC quiet hrs (0630-1400Z). No mil fleet svc avbl. Ltd tsnt svc avbl. Tsnt alert contract backshop maint support may rqr reimbursement and coord with contract officer. Due to large nr of tsnt and exer acft exp delays with tran alert.

NOISE: NS ABTMT quiet hrs in effect 0630-1400Z. Dep climb above 3000' NA until DER.

MILITARY REMARKS: First 132 ft Rwy 21R and 920 ft Rwy 03L grooved concrete; mid 7879 ft cntr 80 ft conc rmg asph.

Rwy 03R-21L steep rising trrn S and E of cntrln; Rwy 03R-21L plows BTR BA thd Rwy 03L-21R when wet; Rwy 03R-21L ungrooved; use ctn for hydroplaning. Rwy 21L 9000'-10000' dist rmg mkr E side NA **RSTD** Sun & hol exp arr fmN; dep fm N winds perm; tfc pat twds E. Bird watch cond mod; ops rstd; tkof or ldg pmsn only when dep & arr avoid bird act; lcl IFR/VFR tfc pat not authorized. Bird watch cond svr; tkof or ldg not authorized wo OG/CC aplv. Hot Cargo Pad unlit; rstd to daylight/VFR ops. Forward firing munitions in revetments 12, 13 & 25 not authorized. All tsnt acft must obtain PPR prior to arr. Refer to Nellis NOTAMS to id avbl airfield svcs window. PPR may be issued up to 7 days prior to, but NLT 48 hrs prior to sked arr. PPR for all exere acft and with wingspans of 132.6' or larger ctc Nellis Support Center DSN 682-5250/5353. (Mon-Fri 1630-0130Z). PPR for non-exercise acft smaller than 132.6' ctc AM Ops DSN 682-4600, C702-652-4601. RON req good for one ngt only, dependent upon ramp space. Tran ftr, non exer acft prkg lmtd to rows 45-46. Acft must adhere to PPR arr block +/- 30 mins of sked ldg. Mtl apch NA durg RF/LFE or aft off SS unless apvd by 57 WG SOF. Acft ptcpg in Nellis sponsored exers/large force exers rqr lcl sponsoring unit. The lcl sponsoring unit will coord maint, prkg, and svcs. PL-2 acft must bring own scy psnl and detail for all large force exers. For cstm & AG, ctc Nellis Support Cntr for acft with wingspans of 132.6' or lgr at DSN 682-5250 or ctc Base Ops for all other acft at DSN 682-4601 with 24 hr PN. Sun and hol tfc exp arr fm north, dep acft north winds pmtd with tfc pat twd east (sunrise mt). Progressive taxi avbl. Acft with code 7 or hyr ctc PTD when 100 NM out. All inbd pax/cargo and DV acft must ctc command post (Raymond 22) on 381.300 NLT 30 mins prior to ldg. B-52 Ops ltd to 380K lb.

CAUTION Incr during BASH Phase II (Apr-May and Aug-Oct). Parachute Jumping. Steeply rising trrn commencing 2.7 NM east of Rwy 03R-21L cntrln up to 3359 MSL. High potential for hydroplaning on both rws of dur wet conds. Acft taxing on Twy D btn Twy F and Rwy 21R use ctn, 4 ft 8 inch hi dstc rmg sign lctd 125 ft north of Twy D cntrln. Hvy acft eng runs pmtd on rwy; req must be sked thru Airfield Mgmt Ops DSN 68204600. Due to FOD problem, 4 eng acft will taxi with outboard engs at idle pwr or shdtn if psbl. Jolly and tsnt helipads misg mandatory hold pos signs. Rwy conds not rprtd. Twy A east TACAN ck point sign nstd. **TFC PAT** Rect tfc pat 3000(1131), overhead tfc pat 3500(1631). **MISC** East side 9000' 1000' distance remaining markers Rwy 21L not avbl. Wx support H24-DSN 682-4744, C702-652-4744. Msn support wx per wing and exer sked typically 1300Z Mon thru 0530Z Fri, clsd weekend and hol, tntst wx aft hr via Davis Monthan 25 OWS-D228-6598/6599, C520-228-6598/6599. Wx obs view of AER 03R/L rstd 190°-330° by flightline bldgs and fac and at ngt due to ramp lgt. Bldgs night flood lgts block the wx obsn view of the AER 03L-03R. No classified mtrl storage avbl at AM ops; classified must be stored in Nellis AFB command post. Tsnt acft shall communicate with Nellis ATC on UHF to max extent psbl due to hvy concentration of acft in the VFR pat. Rsr will be applied to base asgnd/deployed acft.

AIRPORT MANAGER: 702-652-1110

COMMUNICATIONS: SFA ATIS 270.1 PTD 139.3 372.2 (Unreliable 085°-155° byd 35 NM at FL200, 315°-005° byd 40 NM at FL200, 230°-290° byd 55 NM at FL200.)

① **APP CON** 118.125 124.95 273.55 291.725

TOWER 132.55 327.0 **GND CON** 121.8 275.8

② **REP CON** 135.1 350.225 **CLNC DEL** 120.9 289.4 (Opr 1400-0600Z. Full svc avbl dur Nellis flying.)

ACC COMD POST (RAYMOND 22) 320.0 381.3 (381.3 Have quick timing avbl.) **ALCE AMC** 257.35 259.95 (Opr only dur Red Flag deployment/change over/redeployment and other exercises.) **PMSV METRO** 323.9 (Full svc avbl during wx ops hrs.

PMSV unrel 085-155 deg byd 35 NM at or blw FL 200, 315-005 deg byd 40 NM at or blw FL 200, 230-290 deg byd 55 NM at or blo FL 200.)

CONTINUED ON NEXT PAGE

SW, 16 MAY 2024 to 11 JUL 2024

