

WAAS CH 53738 W10A	APP CRS 100°	Rwy Idg TDZE Apt Elev	5001 197 197
--	------------------------	-----------------------------	---


RNAV (GPS) RWY 10

JOHN EDWIN JONES SR FLD/METTER MUNI (MHP)

Baro-VNAV NA. DME/DME RNP-0.3 NA. Helicopter visibility reduction below ¼ SM NA. Use Claxton altimeter setting; when not received, use Vidalia altimeter setting and increase LPV DA to 543, LNAV/VNAV DA to 500, increase all MDA 20 feet, increase LNAV Cat C/D visibility ½ mile and Circling Cat C/D visibility ¼ mile.

MISSED APPROACH: Climb to 700 then climbing right turn to 3000 direct LOTTs and hold.

AWOS-3PT 120.3	CWV AWOS-3 120.075	JACKSONVILLE CENTER 132.925 363.2	UNICOM 123.0 (CTAF) 0
--------------------------	------------------------------	---	---------------------------------





SE-4, 16 MAY 2024 to 13 JUN 2024

SE-4, 16 MAY 2024 to 13 JUN 2024

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 32).

700	3000	LOTTs
-----	------	-------

*LNAV only.



CATEGORY	A	B	C	D
LPV DA		537-1½	340 (400-1½)	
LNAV/VNAV DA		494-1	297 (300-1)	
LNAV MDA	700-1	503 (600-1)	700-1¾	503 (600-1¾)
CIRCLING	820-1 623 (700-1)	880-1 683 (700-1)	1060-2½ 863 (900-2½)	1060-2¾ 863 (900-2¾)

MIRL Rwy 10-28 0

REIL Rwy 10 0