ILS or LOC RWY 30

MIAMI INTL (MIA)

LOC/DME I-DCX	APP CRS	Rwy Idg	7913
111.7	304°	TDZE	8
Chan 54		Apt Elev	9

DME required.
Inop table does not apply.

MALS (A4)

MISSED APPROACH: Climb to 800 then climbing right turn to 2000 on heading 310° and DHP VORTAC R-335 to BRBRA/11.5 DME and hold.

D-ATIS	MIAMI APP CON	MIAMI TOWER	GND CON	CLNC DEL	CPDLC
ARR 119.15 DEP 133.675	124.85 322.3	118.3 256.9	121.8 (8L/8R/12/26L/26R) 348.6 127.5 (9/27/30)	135.35	

RADAR REQUIRED

BRBRA DHP 11.5

155°/335°

R-335

LOCALIZER 111.7
I-DCX
Chan 54

DOLPHIN
113.9 DHP
Chan 86

MSA DHP 25 NM
2100
090° 270°
2900

1049 1049 1049 1049

328 311 164 108 164 306 1049 ± 253 333 432

PECOT
I-DCX 3.9

BIRDD
I-DCX 6.3
RADAR

OLDDE
I-DCX 10.6
RADAR

SHANN
I-DCX 16.7
RADAR
(IF)

1600 304° (4.4) 3000 304° (6.1) 124°

ALTERNATE MISSED APCH FIX
098° 117.1 VKZ
278° R-278
Chan 118
CICIV
VKZ 19

ELEV 9 D TDZE 8

800	2000 hdg 310°	DHP R-335	BRBRA DHP 11.5

VGSI and ILS glidepath not coincident (VGSI Angle 3.00/TCH 71).

*LOC only.



TDZ/CL Rwy 8R
REIL Rwys 8L and 26R
HIRL all Rwys



FAF to MAP 4.8 NM

Knots	60	90	120	150	180
Min:Sec	4:48	3:12	2:24	1:55	1:36

CATEGORY	A	B	C	D
S-ILS 30	258/40 250 (300-¾)			
S-LOC 30	460/40 452 (500-¾)		460/60 452 (500-1¼)	460-1½ 452 (500-1½)

SE-3, 13 JUN 2024 to 11 JUL 2024
SE-3, 13 JUN 2024 to 11 JUL 2024