

LOC/DME RWY 31

LOC I-PLH 111.7	APCH CRS 308°	Rwy ldg 10,000 TDZE 1276 Arprt Elev 1291	[USAF]	TINKER AFB (KTIK)
RADAR required			SALS (A2)	† MISSED APPROACH: Climb straight ahead to 2500, then turn right to 4000 direct I-PLH and TIK 13 DME (BURVE) and hold.
ATIS ★ 270.1	OKE CITY APP CON 120.45 288.325	TOWER 124.45 251.05	GND CON 121.8 275.8	CLNC DEL 119.7 335.8
ASR				

When VGSI inop, procedure NA at night

† Missed approach requires use of RNAV or ATC RADAR monitoring.

LOCALIZER 111.7
I-PLH

CAUTION: VFR flyway West of TIK, sfc to 3000.

EMERG SAFE ALT 100 NM 4700

ELEV 1291	TDZE 1276
-----------	-----------

2500 4000 I-PLH TIK 13

VGSI and Descent angle not coincident. (VGSI Angle 3.00/TCH 71).

CATEGORY	A	B	C	D	E
S-LOC 31*	1740/50 464 (500-1)	1740/60 464 (500-1½)			
CIRCLING**	1840-1 549 (600-1)	1960-1½ 669 (700-1¾)	1980-2¼ 689 (700-2¼)	1960-2¼ 669 (700-2¼)	

SC-1, 13 JUN 2024 to 11 JUL 2024

SC-1, 13 JUN 2024 to 11 JUL 2024

LOC/DME RWY 31