
THRPE THREE DEPARTURE (RNAV)

D-ATIS 125.85 CLNC DEL 124.35 GND CON 121.9 348.6 ROGERS TOWER 119.35 269.45 OKE CITY DEP CON 124.6 266.8

TOP ALTITUDE: ASSIGNED BY ATC

TAKEOFF MINIMUMS

Rwys 13, 17L/R, 18, 31, 35L/R, 36: Standard with minimum climb of 500' per NM to 1800.



THRPE

THRPE

TO STATE OF THE S

NOTE: RADAR required.

NOTE: DME/DME/IRU or GPS required.

NOTE: RNAV 1.

NOTE: Chart not to scale.

SC-1, 13 JUN 2024 to 11 JUL 2024

V

> FLECH

DEPARTURE ROUTE DESCRIPTON

TAKEOFF RWY 13: Climb heading 131° to 1800, then right turn heading 201° or as assigned by ATC, expect RADAR vectors to OLMPC, thence

TAKEOFF RWYS 17L/R, 18: Climb heading 176° to 1800, then right turn heading 201° or as assigned by ATC, expect RADAR vectors to OLMPC, thence

TAKEOFF RWY 31: Climb heading 311° to 1800, then heading 311° or as assigned by ATC, expect RADAR vectors to OLMPC, thence

TÁKEOFF RWYS 35L/R, 36: Climb heading 356° to 1800, then left turn heading 311° or as assigned by ATC, expect RADAR vectors to OLMPC, thence

.... on track 222° to THRPE, then on (transition). Maintain 5000 or as assigned by ATC. Expect filed altitude 10 minutes after departure.

FLECH TRANSITION (THRPE3.FLECH)

GGOLD TRANSITION (THRPE3.GGOLD)