

VORTAC TXO 112.2 Chan 59	APP CRS 242°	Rwy Idg TDZE Apt Elev	7200 4214 4216
--	------------------------	-----------------------------	---


VOR RWY 22

CLOVIS RGNL (CVN)

⚠ DME or Radar required. When local altimeter setting not received, use Cannon AFB altimeter setting and increase all MDA 40 feet; increase S-22 Cat C/D visibility 1/8 mile. VDP NA when using Cannon AFB altimeter setting.

MISSED APPROACH: Climb to 4700 then climbing right turn to 6000 direct TXO VORTAC and hold.

AWOS-3PT 135,375	CANNON APP CON 118,425 352.1	CLNC DEL 119.0	UNICOM 122.8 (CTAF) 0
----------------------------	--	--------------------------	---------------------------------



SW-1, 13 JUN 2024 to 11 JUL 2024

SW-1, 13 JUN 2024 to 11 JUL 2024

ELEV 4216	TDZE 4214
-----------	-----------

REIL Rwy 12 and 30
MIRL Rwy 4-22 and 12-30 0
FAF to MAP 4.5 NM

Knots	60	90	120	150	180
Min:Sec	4:32	3:01	2:16	1:49	1:31

4700	6000	TXO	ZOTLU TXO 7.3 RADAR	TXO VORTAC
↑	↷	⬡		One Minute Holding Pattern

CATEGORY	A	B	C	D
S-22	4600-1	386 (400-1)	4600-1½	386 (400-1½)
<input checked="" type="checkbox"/> CIRCLING	4680-1	464 (500-1)	4700-1½ 484 (500-1½)	4820-2 604 (700-2)