RNAV (GPS) Z RWY 9

GEORGE BUSH INTCNTL/HOUSTON (IAH)

WAAS	APP CRS	Rwy Idg	10000
CH 72926	087°	TDZE	91
W09A		Apt Elev	96

T For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -3°C (27°F) or above 54°C (130°F). For inop MALSR, increase LPV Cat E visibility to RVR 4000, LNAV/VNAV Cat E visibility to 1½ mile, and LNAV Cat C/D/E visibility to 1⅜ mile. Simultaneous approach authorized with Rwys 8L/R. DME/DME RNP-0.3 NA. LNAV procedure NA during simultaneous operations. Use of FD or AP providing RNAV track guidance required during simultaneous operations.
** RVR 1800 authorized with use of FD or AP or HUD to DA.

MALSR

MISSED APPROACH: Climb to 580 then climbing right turn to 3000 direct JEBOX and hold.

D-ATIS	HOUSTON APP CON	HOUSTON TOWER	GND CON	CLNC DEL	CPDLC
124.05	120.05 379.1 EAST 124.35 316.15 WEST	135.15 290.2	118.575	128.1	

RADAR REQUIRED





CATEGORY	A	B	C	D	E
LPV DA**	291/24 200 (200-½)				
LNAV/VNAV DA	525/50 434 (500-1)				
LNAV MDA	580/24 489 (500-½)		580/50 489 (500-1)		

ELEV 96 D TDZE 91



TDZ/CL Rwys 8R, 8L, 15R, 26R, 26L, 27 and 33L
HIRL all Rwys

SC-5, 13 JUN 2024 to 11 JUL 2024
SC-5, 13 JUN 2024 to 11 JUL 2024