


MAYNR TWO DEPARTURE (RNAV)

SE-3, 13 JUN 2024 to 11 JUL 2024

MIAMI DEP CON
125.5 354.1
AWOS-3
118.375
CTAF
122.8

RNAV1 - DME/DME/IRU or GPS.
From SLIPT to MAXIM: RNAV 1 - GPS.
From SLIPT to CANOA: RNAV 1 - GPS.
RADAR required.


TOP ALTITUDE:
ASSIGNED BY ATC



TAKEOFF MINIMUMS

- Rwy 10: Standard with minimum climb of 500'/NM to 2400.
- Rwy 18: Standard with minimum climb of 500'/NM to 1800.
- Rwy 28: Standard with minimum climb of 500'/NM to 1900.
- Rwy 36: Standard with minimum climb of 500'/NM to 2200.

NOTE: Jet aircraft only.
NOTE: Accelerate to 250K until leaving 10000, if unable, advise ATC.



AUSTI
5000

202°

(26)

MAYNR

191°

(26)

MCLAW

243°

(26)

FL180

*1300

185°

(34)

FUNDI

FL180

*1300

265°

(36)

SLIPT

FL180

*1300

275°

(41)

JABOX

FL180

*1300

232°

(15)

MAXIM

FL180

*1300

261°

(41)

CANOA

(CONTINUED ON FOLLOWING PAGE)

SE-3, 13 JUN 2024 to 11 JUL 2024

NOTE: Chart not to scale.

MAYNR TWO DEPARTURE (RNAV)