

**LOUISVILLE**

**BOWMAN FLD** (LOU)(KLOU) P (AR) 5 SE UTC-5(-4DT) N38°13.68' W85°39.82'

**ST LOUIS**  
L-27E  
IAP, AD

546 B NOTAM FILE LOU

**RWY 06-24:** H4358X75 (ASPH) S-30 MIRL 0.3% up SW

**RWY 06:** PAPI(P2L)—GA 3.5° TCH 45'. Thld dsplcd 848'. Tree.

**RWY 24:** REIL. PAPI(P2L)—GA 3.0° TCH 53'. Thld dsplcd 310'. Tree.

**RWY 15-33:** H3580X75 (ASPH) S-30 MIRL 0.6% up NW

**RWY 15:** PAPI(P2L)—GA 3.5° TCH 45'. Thld dsplcd 206'.

**RWY 33:** REIL. PAPI(P2L)—GA 3.25° TCH 45'. Thld dsplcd 342'. Road.

**RUNWAY DECLARED DISTANCE INFORMATION**

**RWY 06:** TORA-4047 TODA-4357 ASDA-4316 LDA-3469

**RWY 15:** TORA-3238 TODA-3579 ASDA-3579 LDA-3373

**RWY 24:** TORA-3509 TODA-4357 ASDA-4165 LDA-3856

**RWY 33:** TORA-3373 TODA-3579 ASDA-3466 LDA-3125

**SERVICE:** S4 FUEL 100LL, JET A OX 1, 2, 3, 4 LGT Actvt MIRL Rwy 06-24 & Rwy 15-33—CTAF. **MILITARY—FUEL** (NC-100LL, A)

**AIRPORT REMARKS:** Attended 1200-0300Z±. Stage 3 compliance rqrd for turbojet; PPR for acft over 30,000 lbs GWT— Amgr. Birds on & invof arpt durg dalgt hr. Compass rose lctd at admin bldg not for compass calibration use. Trng ops NA when ATCT clsd. 24 hr PPR for mil rotary wing. Obstns & trees in all apch sfcs. ADCUS flt notification svc avbl. NOTE: See Special Notices—Terminal Area Graphic Notice.

**AIRPORT MANAGER:** 502-851-5906

**WEATHER DATA SOURCES:** ASOS 118.275 (502) 473-0693.

**COMMUNICATIONS:** CTAF 119.5 ATIS 124.15 UNICOM 122.95

LOUISVILLE RCO 122.2 (LOUISVILLE RADIO)

Ⓡ LOUISVILLE APP/DEP CON 132.075

TOWER 119.5 (1200-0300Z±) GND CON 121.8 CLNC DEL 118.9

**CLEARANCE DELIVERY PHONE:** For CD when ATCT clsd, ctc sdf ATCT 502-375-7499.

**AIRSPACE:** CLASS D svc 1200-0300Z±; other times CLASS E.

**RADIO AIDS TO NAVIGATION:** NOTAM FILE LOU.

(T) DME 112.2 BQM Chan 59 N38°13.81' W85°39.88' at fld. 542.

LOUISVILLE (H) (H) VORTACW 114.8 IIU Chan 95 N38°06.21' W85°34.65' 330° 8.5 NM to fld. 720/1E.

VOR unusable:

001°-025°

026°-090° blo 10,000'

100°-150° blo 9,000'

151°-180° blo 7,000'

275°-330° byd 30 NM blo 4,000'

TACAN AZIMUTH unusable:

225°-275° blo 5,000'

DME unusable:

225°-275° blo 5,000'

