

ZELAN FOUR DEPARTURE (RNAV)

**TOP ALTITUDE:
10000**

D-ATIS 125.55

CLNC DEL 118.1

CPDLC

GND CON

121.9 254.4 (Rwys 8L-26R, 8R-26L)

121.75 254.4 (Rwys 9L-27R, 9R-27L)

121.65 254.4 (Rwy 10-28)

ATLANTA TOWER

119.1 254.4 (Rwy 8L-26R)

125.325 254.4 (Rwy 8R-26L)

119.3 254.4 (Rwy 9R-27L)

123.85 254.4 (Rwy 9L-27R)

119.5 254.4 (Rwy 10-28)

ATLANTA DEP CON

133.475 281.425 (Rwys 8L-26R, 8R-26L)

125.65 281.425 (Rwys 9L-27R, 9R-27L)

121.225 281.425 (Rwy 10-28)

NASHVILLE
BNA

CEASE

EMAHH

RESPE

GLAZR

JAACE

LEDRR

SMTH

BOBBD

RAFTN

COLVN

HUCHH

PENCL

VARNM

PADGT

SMKEY

WURLD

ZELAN
6000 250K

MPASS

TAKEOFF MINIMUMS

Rwy 27R: Standard with minimum climb of 500' per NM to 1527.

CPARK

- NOTE: For turbojets only.
- NOTE: RNP-1.
- NOTE: RF required.
- NOTE: GPS required.
- NOTE: If unable to accept climb rate, advise clearance delivery on initial contact.
- NOTE: Use departure frequency depicted unless otherwise assigned.
- NOTE: Accelerate to 250K, if unable, advise both tower and departure control on initial contact.
- NOTE: Transponder code will be issued via PDC or Atlanta clearance delivery.
- NOTE: Aircraft at midfield ramps will advise ramp towers of departure SID prior to pushback. Upon receipt of ATC clearance (from ATL clearance delivery), readback only your call sign and transponder code, unless you have a question.

(NARRATIVE ON FOLLOWING PAGE)

NOTE: Chart not to scale.

ZELAN FOUR DEPARTURE (RNAV)

SE-4, 11 JUL 2024 to 08 AUG 2024

SE-4, 11 JUL 2024 to 08 AUG 2024