



LOC/DME I-SSX <b>109.35</b> Chan 30 (Y)	APP CRS <b>201°</b>	Rwy Idg TDZE <b>8000</b> <b>551</b> Apt Elev <b>599</b>
---	------------------------	---

# ILS or LOC/DME RWY 20L

NASHVILLE INTL (BNA)

<b>▽</b> Simultaneous approach authorized with Rwy 20R. <b>▲</b> DME required. **RVR 1800 authorized with the use of FD or AP or HUD to DA.	MALSRR	MISSED APPROACH: Climb to 1300 then climbing left turn to 3000 on heading 040° and BNA VORTAC R-072 to LENON/BNA 25.1 DME and hold.
	D-ATIS <b>135.1</b>	NASHVILLE APP CON <b>118.4 360.7</b>
GND CON <b>121.9 348.6</b>		CLNC DEL <b>126.05</b>
CPDLC		

## RADAR REQUIRED



CATEGORY	A	B	C	D
S-ILS 20L	** 751/24 200 (200-½)			
S-LOC 20L	980/24	429 (400-½)	980/40	429 (400-¾)
<b>C</b> CIRCLING	1100-1 501 (600-1)	1120-1 521 (600-1)	1200-1¾ 601 (700-1¾)	1380-2½ 781 (800-2½)

SE-1, 11 JUL 2024 to 08 AUG 2024

SE-1, 11 JUL 2024 to 08 AUG 2024