

LOC/DME I-SZK
111.1
Chan **48**

APP CRS
072°

Rwy Idg
TDZE **1175**
Apt Elev **1175**

LDA Z RWY 6

ROANOKE/BLACKSBURG RGNL (WOODRUM FLD) (R.O.A)

For inop MALSR, increase S-LDA/GS 6 all Cats visibility to ¾ mile. Missed approach requires a minimum climb of 350 feet per NM to 3600, if unable to meet climb gradient, see LDA Y Rwy 6.

13°C

MALSR

MISSED APPROACH: Climb to 1800 then climbing right turn to 5000 on ODR VOR R-155 to PARTE INT/LYH 28.6 DME and hold, continue climb-in-hold to 5000.

ATIS 132.375	ROANOKE APP CON 126.9 339.8	ROANOKE TOWER 118.3 257.8	GND CON 121.9 257.8	CLNC DEL 119.7
------------------------	---------------------------------------	-------------------------------------	-------------------------------	--------------------------

Procedure NA for arrivals on PSK
VORTAC airway radials 021 CW 100.

ROANOKE, VIRGINIA

ROANOKE/BLACKSBURG RGNL (WOODRUM FLD) (R.O.A)

Orig-A 25JAN24

37°20'N-79°59'W

LDA Z RWY 6