

SEVYR THREE DEPARTURE

AL-365 (FAA)

SALT LAKE CITY INTL (SLC)

SALT LAKE CITY, UTAH

D-ATIS

124.75 125.625

CLINC DEL

127.3 379.975

CPDLC

SALT LAKE CITY DEP CON

128.1 307.05

TAKEOFF MINIMUMS

Rwys 14, 16L/R, and 17: NA - Operational.

Rwy 32: 400-1 or standard with a minimum climb of 450' per NM to 7500.

Rwys 34L/R and 35: Aircraft assigned heading 263° CW through 322° standard with a minimum climb of 260' per NM to 7500.

Aircraft assigned heading 323° CW through 343° standard with a minimum climb of 340' per NM to 7500.

NOTE: This is a RADAR vector departure to assigned route or fix.

NOTE: For turbojet and turboprop aircraft only.

NOTE: RADAR required.

TOP ALTITUDE:
10000

10000

WASATCH
116.8 TCH ---
Chan 115

11500

DELTA
116.1 DTA
Chan 108

MILFORD
112.1 MLF
Chan 58

COALDALE
117.7 OAL :E..
Chan 124

(CONTINUED ON FOLLOWING PAGE)

NOTE: Chart not to scale.

SW-4, 11 JUL 2024 to 08 AUG 2024

SEVYR THREE DEPARTURE

(SEVYR3.SEVYR) 17AUG17

SALT LAKE CITY, UTAH
SALT LAKE CITY INTL (SLC)