APP CRS	Rwy ldg	8505
217°	TDZE	770
	Apt Elev	809

RNAV (RNP) X RWY 22

SAN ANTONIO INTL (SAT)

RNP AR APCH - GPS.

For uncompensated Baro-VNAV systems, procedure NA below -5°C or above 54°C.

MISSED APPROACH: (Do not exceed 195K until IMIKE) Climb to 3100 direct IMIKE and on track 137° EMBOW and hold.

D-ATIS	SAN ANTONIO APP CON	SAN ANTONIO TOWER	GND CON	CLNC DEL	CPDLC
118.9	125.1 307.0	119.8 257.8	121.9 348.6	126.7	



MISSED APCH FIX

ELEV 809	D	TDZE 770



3100	IMIKE	tr 137°	EMBOW

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 85).



CATEGORY	A	B	C	D
RNP 0.15 DA		1070-⅞	300 (300-⅞)	
RNP 0.30 DA		1222-1⅜	452 (500-1⅜)	

AUTHORIZATION REQUIRED

TDZ/CL Rwy 13R
REIL Rwys 13L, 22 and 31R
HIRL Rwys 4-22 and 13R-31L
MIRL Rwy 13L-31R

SC-3, 11 JUL 2024 to 08 AUG 2024
SC-3, 11 JUL 2024 to 08 AUG 2024