

WAAS
CH **72932**
W08A

APP CRS
081°

Rwy Idg
TDZE **589**
Apt Elev **595**

RNAV (GPS) RWY 8

SAN MARCOS RGNL (HYI)

RNP APCH.


▼

⚠

Circling NA for Cat E SW of Rwy 13-31. Rwy 8 helicopter visibility reduction below ¾ SM NA. Baro-VNAV NA when using New Braunfels altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C or above 54°C. VDP NA with New Braunfels altimeter setting. When local altimeter setting not received, use New Braunfels altimeter setting and increase LPV DA to 882, LNAV/VNAV DA to 953 and increase all MDA 60 feet; increase LNAV Cat C/D/E and Circling Cat C/D visibility ¼ SM.

MISSED APPROACH:
Climb to 3000 direct QIMB and hold.

ATIS ★ 120.825	AUSTIN APP CON 119.0 370.85	SAN MARCOS TOWER★ 126.825 (CTAF) 0	GND CON 120.125	CLNC DEL 120.125	CLNC DEL 121.35 (when twr closed)
--------------------------	---------------------------------------	---	---------------------------	----------------------------	--



6 NM Holding Pattern

RAJRY

KEDCE

NUHOS 3.1 NM to RW08

*1.5 NM to RW08

RW08

GP 3.00° TCH 55

2400

*1620

7.2 NM

2.4 NM

1.6 NM

1.5 NM

3000

QIMB

*LNAV only.

CATEGORY	A	B	C	D	E
LPV DA	839-1 250 (300-1)				
LNAV/VNAV DA	910-1 321 (400-1)				
LNAV MDA	1120-1 531 (600-1)	1120-1½ 531 (600-1½)			
CIRCLING	1120-1 525 (600-1)	1240-1¾ 645 (700-1¾)	1320-2¼ 725 (800-2¼)	1340-2¾ 745 (800-2¾)	

