



TAKEOFF OBSTACLE NOTES

SW-1, 11 JUL 2024

đ

08 AUG 2024

112.4 JNC :::... Chan 71

- Rwy 11: Light poles beginning 7' from DER, 55' left of centerline, up to 3' AGL/4863' MSL. Light poles 8' from DER, 54' right of centerline, 1' AGL/4862' MSL. Poles beginning 251' from DER, 285' left of centerline, up to 20' AGL/4883' MSL.
- Rwy 29: Vertical structure 151' from DER, 432' right of centerline, 22' AGL/4846' MSL. Navaid, tower beginning 266' from DER, 398' right of centerline, up to 43' AGL/4865' MSL.

TAKEOFF MINIMUMS

Rwy	4:	NA -	Obst	acles		

- Rwy 22: NA Obstacles, facility reception (JNC VOR/DME).
- Rwy 11: Standard with minimum climb of 235' per NM to 7400.
- Rwy 29: Standard with minimum climb of 225' per NM to 8000.

NOTE: Chart not to scale.

DEPARTURE ROUTE DESCRIPTION

TAKEOFF RUNWAY 11: Climb on heading 116° to 6600, then climbing right turn to heading 240° until receiving JNC VOR/DME, then proceed direct JNC VOR/DME, thence

<u>TAKEOFF RUNWAY 29:</u> Climb on heading 296° to 7000, then climbing left turn to heading 240° until receiving JNC VOR/DME, then proceed direct JNC VOR/DME, thence

.... Cross JNC VOR/DME at or above MEA/MCA for route of flight. If required, continue climb in JNC holding pattern to cross JNC at or above MEA/MCA for route of flight.

NSA INC 25 NL

11400

10100

6600