

WAAS CH <b>86936</b> <b>W14A</b>	APP CRS <b>141°</b>	Rwy ldg <b>5600</b> TDZE <b>953</b> Apt Elev <b>953</b>
--	------------------------	---



# RNAV (GPS) RWY 14

NEWTON MUNI-EARL JOHNSON FLD (TNU)

**⚠** DME/DME RNP-0.3 NA. When local altimeter setting not received use Des Moines altimeter setting and increase all DA/MDA 80 feet; increase LPV and LNAV/VNAV all Cats and LNAV Cats C/D and Circling Cat C/D visibility ¼ mile. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -13°C (9°F) or above 54°C (130°F). Rwy 14 helicopter visibility reduction below ¾ SM NA. Baro-VNAV and VDP NA when using Des Moines altimeter setting.

MISSED APPROACH: Climb to 2700 direct UBHIT and hold.

AWOS-3 <b>132.275</b>	DES MOINES APP CON <b>123.9 307.15</b>	CLNC DEL <b>126.3</b>	UNICOM <b>122.8 (CTAF) 0</b>
--------------------------	---	--------------------------	---------------------------------



ELEV 953	TDZE 953	UBHIT  4 NM			
4 NM Holding Pattern 3100 ← 321° 141° →		KOWDO 2600 EBSUH 2600 * 1.3 NM to RWY14 RWY14 * LNAV only.			
GP 3.00° TCH 39		6 NM      3.8 NM      1.3 NM			
CATEGORY	A	B	C	D	
LPV DA	1203-7/8		250 (300-7/8)		
LNAV/VNAV DA	1203-7/8		250 (300-7/8)		
LNAV MDA	1420-1 467 (500-1)		1420-1 3/8 467 (500-1 3/8)		
<b>C</b> CIRCLING	1420-1 467 (500-1)	1440-1 1/2 487 (500-1 1/2)	1520-1 1/2 567 (600-1 1/2)	1600-2 647 (700-2)	

NC-3, 11 JUL 2024 to 08 AUG 2024

NC-3, 11 JUL 2024 to 08 AUG 2024