| WAAS | APP CRS | Rwy Idg | 4201 |
|---|---|---|---|
| CH 72709 | 272° | TDZE | 912 |
| W27A | | Apt Elev | 913 |

# RNAV (GPS) RWY 27

## DE KALB TAYLOR MUNI (DKB)

When local altimeter setting not received, use Aurora altimeter setting and increase all DA 61 feet and all MDA 80 feet; increase all LPV and LNAV/VNAV visibilities, LNAV Cats C/D visibility, and Circling Cats C/D visibility ¼ mile. Baro-VNAV NA when using Aurora altimeter setting. VDP NA when using Aurora altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16° C (4°F) or above 47° C (116° F). DME/DME RNP-0.3 NA.

MISSED APPROACH: Climb to 3000 direct JADIS and via 305° track to SIMMN and hold.

| AWOS-3 | CHICAGO APP CON | UNICOM |
|---|---|---|
| 119.075 | 133.5 349.0 | 122.7 (CTAF) L |










| CATEGORY | A | B | C | D |
|---|---|---|---|---|
| LPV DA | 1162-¾ 250 (300-¾) | | | |
| LNAV/VNAV DA | 1317-1½ 405 (500-1½) | | | |
| LNAV MDA | 1360-1 448 (500-1) | | 1360-1¼ 448 (500-1¼) | 1360-1½ 448 (500-1½) |
| CIRCLING | 1360-1 447 (500-1) | 1500-1 587 (600-1) | 1600-2 687 (700-2) | 1740-2¾ 827 (900-2¾) |

REIL Rwys 9, 20 and 27 L
MIRL Rwys 2-20
MIRL Rwys 9-27 L



EC-3, 11 JUL 2024 to 08 AUG 2024
EC-3, 11 JUL 2024 to 08 AUG 2024