RNAV (GPS) RWY 32

PEARLAND RGNL (LVJ)

WAAS	APP CRS	Rwy Idg 4313
CH 93621	322°	TDZE 43
W32A		Apt Elev 44

Circling to Rwy 14 NA at night. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -1°C (31°F) or above 54°C (130°F). When local altimeter setting not received, use William P Hobby altimeter setting and increase all DA 18 feet and all MDA 20 feet, increase LNAV/VNAV visibilities all Cats ⅛ mile. VDP and Baro-VNAV NA when using William P Hobby altimeter setting. DME/DME RNP-0.3 NA. Helicopter visibility reduction below ¾ SM NA.

MISSED APPROACH: Climb to 500 then climbing left turn to 3000 direct ACOLA and hold.

ASOS	HOUSTON APP CON	CLNC DEL	UNICOM
118.525	134.45 284.0	124.0	122.725 (CTAF) L



ELEV 44 TDZE 43





CATEGORY	A	B	C	D
LPV DA	293-⅞	250 (300-⅞)	NA	
LNAV/VNAV DA	310-⅞	267 (300-⅞)	NA	
LNAV MDA	400-1	357 (400-1)	NA	
C CIRCLING	500-1 456 (500-1)	660-1 616 (700-1)	NA	

SC-5, 11 JUL 2024 to 08 AUG 2024
SC-5, 11 JUL 2024 to 08 AUG 2024