


WAAS CH 73007 W30A	APP CRS 299°	Rwy Idg TDZE Apt Elev	5500 2432 2432
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 30

CALDWELL EXEC (EUL)

RNP APCH.	MISSED APPROACH: Climb to 5000 direct REDVE and hold.
Rwy 30 helicopter visibility reduction below ¾ SM NA. Baro-VNAV NA when using Boise altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -19°C or above 44°C. When local altimeter setting not received, use Boise altimeter setting and increase all DA/MDA 120 feet and all visibilities ½ mile.	

AWOS-3PT 135.075	BIG SKY APP CON 119.6 269.4	UNICOM 123.0 (CTAF) 0
----------------------------	---------------------------------------	--



ELEV 2432 TDZE 2432		5000 REDVE			
*LNAV only		CABEP 2.1 NM to RW30			
RW30		BABTE			
ADEXE		5 NM Holding Pattern			
3140°		299° 119° 5000			
2.1 NM 2.9 NM 6.1 NM		GP 3.00° TCH 45			
CATEGORY	A	B	C	D	
LPV DA	2687-1 255 (300-1)				
LNAV/VNAV DA	2822-1¼ 390 (400-1¼)				
LNAV MDA	2880-1 448 (500-1)	2880-1⅓ 448 (500-1⅓)	2880-1½ 448 (500-1½)		

NW-1, 11 JUL 2024 to 08 AUG 2024

NW-1, 11 JUL 2024 to 08 AUG 2024