

WAAS CH 93518 W16A	APP CRS 164°	Rwy Idg TDZE Apt Elev	5089 2433 2437
--	------------------------	-----------------------------	---


RNAV (GPS) RWY 16

MADRAS MUNI (S33)


Baro-VNAV NA when using Redmond altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -19°C (-2°F) or above 54°C (130°F). Rwy 16 helicopter visibility reduction below 3/4 SM NA. DME/DME RNP-0.3 NA. When local altimeter setting not received, use Redmond altimeter setting and increase all DA and MDA 580 feet; increase LPV all Cats visibility 2 2/3 SM, LNAV/VNAV all Cats visibility 2 3/4 SM, LNAV and Circling Cat A visibility 1/4 SM, LNAV and Circling Cat B visibility 1/2 SM, and increase LNAV and Circling Cat C visibility 1 1/4 SM.

MISSED APPROACH: Climb to 7000 direct HUKRI and on track 074° to JOREM and on track 042° to ZEMAB and hold.

AWOS-3PT 132.425	SEATTLE CENTER 126.15 269.475	UNICOM 122.8 (CTAF) 📻
----------------------------	---	--



	HETIM	7000 HUKRI	JOREM	ZEMAB
		↑	tr 074°	tr 042°
	5500			
	164°			
	4600			
	4000			
	3.8 NM	2.4 NM	1.6 NM	3.2 NM
CATEGORY	A	B	C	D
LPV DA	2783-1 1/8	350 (400-1 1/8)		NA
LNAV/VNAV DA	2843-1 3/8	410 (500-1 3/8)		NA
LNAV MDA	3040-1	607 (700-1)	3040-1 3/4 607 (700-1 3/4)	NA
CIRCLING	3040-1	603 (700-1)	3040-1 3/4 603 (700-1 3/4)	NA



NW-1, 11 JUL 2024 to 08 AUG 2024

NW-1, 11 JUL 2024 to 08 AUG 2024