RNAV (RNP) Z RWY 17L

WILL ROGERS WORLD (OKC)

APP CRS	Rwy Idg	TDZE	Apt Elev
176°	9802	1287	1296

ASR

For uncompensated Baro-VNAV systems, procedure NA below -12°C (11°F) or above 54°C (130°F). GPS required. Simultaneous approach authorized with Rwy 17R. Use of FD or AP providing RNAV track guidance required during simultaneous operations.

MALSR

MISSED APPROACH: Climb to 5000 on track 176° to JAVXE and hold, continue climb-in-hold to 5000.

D-ATIS	OKE CITY APP CON	ROGERS TOWER	GND CON	CLNC DEL
125.85	124.6 266.8	119.35 269.45	121.9 348.6	124.35

RADAR required for procedure entry at ATREC.

(IAF) ATREC (RNP 0.40) 5000

4000 176° (3.5)

(IF) GOLFS 210K

3000 176° (3.9)

HAMDO

WUVMA 210K

RADAR required for procedure entry at HIPES.

(IF) FLAPP (RF Required) (RNP 0.40) 5000 210K

4000 086° (4.9)

4000 086° (0.8)

MERTE

JINTA

3500 (1.6)

DONMO

4000 (4)

3000 (2.3)

ADWOW

SIWHU

3000 (1.7)

3500 266° (5)

(IF) HIPES (RF Required) (RNP 0.80) 5000

2300 176° (2.3)

2300 (2.2)

3500 (3.9)

2046

(FAF) SCORY

ISAKE

5000 356° (3.3)

(IF) WWILL (RF Required) (RNP 0.40) 6000 210K

176° (3)

4700 356° (4.1)

1608

RW17L

1881

1416

1953

(IF) PALMR (RF Required) (RNP 0.80) 6000 210K

176° (14.3)

MISSED APCH FIX JAVXE 356° 176° 5 NM

MSA RW17L 25 NM 3800

2758

ELEV 1296 D TDZE 1287

176°

TWR 1436

1340

7800 X 150

9803 X 150

9801 X 150

3078 X 75

3.3% up

35L

35R

5000 | tr 176° | JAVXE

See planview for multiple IF locations.

SCORY 2300

RW17L 176° 2300

GP 3.00° TCH 59

3 NM

CATEGORY	A	B	C	D
RNP 0.11 DA	1555/24 268 (300-½)			
RNP 0.20 DA	1643/34 356 (400-⅝)			
RNP 0.30 DA	1724/49 437 (500-1)			

AUTHORIZATION REQUIRED

REIL Rwys 13 and 31
TDZ/CL Rwy 35R
MIRL Rwy 13-31
HIRL Rwys 17L-35R and 17R-35L

SC-1, 08 AUG 2024 to 05 SEP 2024
SC-1, 08 AUG 2024 to 05 SEP 2024