

# SEVYR THREE DEPARTURE

AL-365 (FAA)

SALT LAKE CITY INTL (SLC)  
SALT LAKE CITY, UTAH

**TOP ALTITUDE:  
10000**


WASATCH  
116.8 TCH  
Chan 115

11500

DELTA  
116.1 DTA  
Chan 108

MILFORD  
112.1 MLF  
Chan 58

COALDALE  
117.7 OAL  
Chan 124



FL280  
193°  
(80)

EDETH

FL280  
170°  
(80)

SEVYR

FL280  
170°  
(52)

FL310  
238°  
(241)

R-05A

1148

SW-4, 08 AUG 2024 to 05 SEP 2024

SW-4, 08 AUG 2024 to 05 SEP 2024

(CONTINUED ON FOLLOWING PAGE)

NOTE: Chart not to scale.

**TAKEOFF MINIMUMS**  
 Rwy 14, 16L/R, and 17: NA - Operational.  
 Rwy 32: 400-1 or standard with a minimum climb of 450' per NM to 7500.  
 Rwy 34L/R and 35: Aircraft assigned heading 263° CW through 322° standard with a minimum climb of 260' per NM to 7500.  
 Aircraft assigned heading 323° CW through 343° standard with a minimum climb of 340' per NM to 7500.

NOTE: This is a RADAR vector departure to assigned route or fix.  
 NOTE: For turbojet and turboprop aircraft only.  
 NOTE: RADAR required.