

VORTAC SVM

114.3

Chan 90

APP CRS

213°

Rwy Idg

3505

TDZE

831

Apt Elev

839

VOR RWY 24



ANN ARBOR MUNI (ARB)


⚠ Inop table does not apply. Rwy 24 helicopter visibility reduction below ¾ SM NA.

⚠ When local altimeter setting not received, use Willow Run altimeter setting and increase all MDAs 40 feet and increase visibility S-24 Cat C/D visibility ⅓ SM and Circling Cat C/D visibility ¼ SM. Circling NA to Rwys 12 and 30.

MISSED APPROACH: Climbing left turn to 3000 direct SVM VORTAC and hold.

ATIS 134.55	DETROIT APP CON 118.95 284.0	ANN ARBOR TOWER ★ 120.3 (CTAF) 0	GND CON 121.6	CLNC DEL 121.6	UNICOM 123.0
----------------	---------------------------------	-------------------------------------	------------------	-------------------	-----------------



DME or RADAR REQUIRED					
3000 	SVM 	VGSI and descent angles not coincident (VGSI Angle 3.00/TCH 20).			
One Minute Holding Pattern					
					
CATEGORY	A		B	C	D
S-24	1460-1 629 (700-1)		1460-1¾ 629 (700-1¾)	1460-1¾ 629 (700-1¾)	
CIRCLING	1500-1 661 (700-1)		1500-1¾ 661 (700-1¾)	1640-2½ 801 (900-2½)	