TEXAS 313

FORT WORTH MEACHAM INTL (FTW)(KFTW) 5 N UTC-6(-5DT) N32°49.19′ W97°21.75′ 710 B TPA—See Remarks ARFF Index—See Remarks NOTAM FILE FTW

RWY16-34: H7502X150 (CONC-GRVD) S-80, D-100, 2S-127, 2D-190, 2D/2D2-350 PCN 30 R/C/W/U HIRL 0.5% up N RWY16: MALSR. PAPI(P4R)—GA 3.0° TCH 59°. RVR-T Pole.

COPTER H–6H, L–17C, A IAP, AD

DALLAS-FT WORTH

RWY 34: MALS. RVR-R Rgt tfc.

RWY17-35: H4005X75 (ASPH) S-12.5, D-50 PCN 11 F/C/X/U MIRL RWY17: PAPI(P2L)—GA 3.75° TCH 56'. Berm. Rgt tfc.


RWY 35: PAPI(P2L)-GA 3.25° TCH 43'.

RUNWAY DECLARED DISTANCE INFORMATION

RWY 16: TORA-7502 TODA-7502 ASDA-7502 LDA-7502 **RWY 34:** TORA-7502 TODA-7502 ASDA-7455 LDA-7455

 $\begin{array}{lll} \textbf{SERVICE:} & 84 & \textbf{FUEL} & 100\text{LL}, \ \text{JET A}, \ A1+ & \textbf{OX}1, \ 3 & \textbf{LGT} \ \text{Rwy} \ 17-35 \ \text{LED} \\ & \text{lgt can appr brgtr than Rwy} \ 16-34; \ \text{ensure cor rwy alnmt.} \end{array}$

AIRPORT REMARKS: Attended continuously. Birds on and invof arpt. Rwy 09–27 CLOSED indef. Class IV, ARFF Index A. ARFF Index B avbl all users with PPR. Helo skidding opns prohibited on Rwy 17–35. If skidding is rqrd, coord with ATCT to use Twy B. Rwy 17–35 Twys B, B1, C and D west of Rwy 16–34, Twy M east of Twy A, H, J, Txl G SE of Txl N clsd to acft with more than 30 psgr seats. Rwy 17–35 designed for acft with wingspan of 49 ft or less. Twys B and B1 designed for acft with wingspan less than 79 ft. Rwy 16–34 and Twys A, A1, and M designed for acft with wingspan less than 171 ft. All



AIRPORT MANAGER: 817 392-5400

WEATHER DATA SOURCES: ASOS (817) 740-3346

COMMUNICATIONS: ATIS 120.7

RCO 122.6 (FORT WORTH RADIO)

® RGNL APP/DEP CON 118.1 124.3 125.2 125.8 125.9 135.975 (North) 118.1 125.8 135.975 (South) 124.3 125.2

MEACHAM TOWER 118.3 GND CON 121.9 CLNC DEL 124.65

AIRSPACE: CLASS D.

VOR TEST FACILITY (VOT) 108.2

RADIO AIDS TO NAVIGATION: NOTAM FILE FTW.

RANGER (VH) (H) VORTACW 115.7 FUZ Chan 104 N32°53.37′ W97°10.77′ 240° 10.1 NM to fld. 639/6E. VOR unusable:

275°-290° bvd 40 NM

317°-327° byd 40 NM

MUFIN NDB (LOMW) 365 FT N32°53.59′ W97°22.40′ 165° 4.4 NM to fld. 744/8E.

ILS/DME 109.9 I-FTW Chan 36 Rwy 16. Class IT. LOM MUFIN NDB. DME also serves Rwy 34.

ILS/DME 109.9 I-UXT Chan 36 Rwy 34. Class IB. DME also serves Rwy 16.

HELIPAD H1: H35X35 (CONC) HELIPAD H2: H35X35 (CONC)

HELIPORT REMARKS: H1 and H2 helipads are VMC dalgt use only; non–movement area. Hels repositioning byd imt prkg apron and under their own pwr must ctc ATC.