

MIAMI INTL (MIA)(KMIA) 8 NW UTC-5(-4DT) N25°47.72' W80°17.41' **MIAMI**
 9 B AOE Class I, ARFF Index E NOTAM FILE MIA **H-8I, L-23C, A**
RWY 09-27: H13016X150 (ASPH-GRVD) S-120, D-250, 2S-175, 2D-550, 2D/2D2-1120 **IAP, AD**
 PCR 851 F/A/X/T HIRL CL
RWY 09: MALS. PAPI(P4L)—GA 3.0° TCH 72'. RVR-TMR Thld dspcd 1358'. Railroad. Rgt tfc.
RWY 27: MALS. PAPI(P4L)—GA 3.0° TCH 71'. RVR-TMR Thld dspcd 261'.
RWY 08R-26L: H10506X200 (ASPH-GRVD) S-120, D-250, 2S-175, 2D-550, 2D/2D2-1120 PCR 851 F/A/X/T HIRL
 CL
RWY 08R: MALS. TDZL. PAPI(P4L)—GA 3.0° TCH 77'. RVR-TR
RWY 26L: MALS. PAPI(P4L)—GA 3.0° TCH 73'. RVR-TR Rgt tfc.
RWY 12-30: H9360X150 (ASPH-GRVD) S-120, D-250, 2S-175, 2D-550, 2D/2D2-1120 PCR 780 F/A/X/T HIRL CL
RWY 12: MALS. PAPI(P4R)—GA 3.0° TCH 72'. RVR-TR Tower.
RWY 30: MALS. PAPI(P4L)—GA 3.0° TCH 71'. RVR-TR Thld dspcd 945'. Tree.
RWY 08L-26R: H8600X150 (ASPH-GRVD) S-120, D-250, 2D-550, 2D/2D2-1120 PCR 711 F/A/X/T HIRL CL
RWY 08L: REIL. PAPI(P4L)—GA 3.0° TCH 60'.
RWY 26R: REIL. PAPI(P4L)—GA 3.0° TCH 60'.
LAND AND HOLD-SHORT OPERATIONS

LDG RWY	HOLD-SHORT POINT	AVBL LDG DIST
RWY 09	12-30	9749
RWY 12	09-27	8100

RUNWAY DECLARED DISTANCE INFORMATION
RWY 08L:TORA-8600 TODA-8600 ASDA-8600 LDA-8600
RWY 08R:TORA-10506 TODA-10506 ASDA-10506 LDA-10506
RWY 09: TORA-13016 TODA-13016 ASDA-12755 LDA-11397
RWY 12: TORA-9355 TODA-9355 ASDA-8579 LDA-8579
RWY 26L:TORA-10506 TODA-10506 ASDA-10220 LDA-10220
RWY 26R:TORA-8600 TODA-8600 ASDA-8600 LDA-8600
RWY 27: TORA-13016 TODA-13016 ASDA-13016 LDA-12755
RWY 30: TORA-9355 TODA-9355 ASDA-8853 LDA-7913
SERVICE: S4 FUEL 100, JET A 0X 1, 2, 3, 4
NOISE: Close-in noise abatement dep profile to be used by A319/320/321, A330-200/300, B727-200, B737-800/900, B767-200/300/400/700, B747-800, B777-300/77L/77W, and MD-11. Dsnt noise abatement dep profile to be used by all other turbojet acft. All tbtj acft are reqd to use dsnt noise abatement dep profile (NADP-2) from all rwys.
AIRPORT REMARKS: Attended continuously. Birds on and invof arpt. CLOSED non-engine acft. Rwy 08L-26R CLOSED 0800-1700Z± when Rwy 08R-26L and Rwy 09-27 are in use. Rwy 12-30 CLOSED 0800-1700Z± when Rwy 08R-26L and Rwy 09-27 are in use. No int dep auth wo PPR fm amgr. Acft with wingspan greater than 78' are prohibited from entering the GAC ramp. Acft with a wingspan greater than 171' are prohibited from taxiing on Twy P, east of Twy U, except adg VI acft complying with MIA adg VI operational plan when adj airside svc road is clsd to traffic. PPR for inbd mil flts 100 NM on freq 130.5. All diversion ctc frequency 130.5 upon arrival. All medical emerg arr, with the exception of air ambulance flts, must secure doors until ARFF is on scene. Acft with a wingspan gtr than 171' are prohibited fm tbg on Twy P E of Twy U, except adg VI acft complying with MIA ADG VI operational plan when adj airside svc road is clsd to tfc. ASDE-X in use. Operate transponders with altitude reporting mode and ADS-B (if equipped) enabled on all airport surfaces. US CBP and EAPIS avbl. Flight Notification Service (ADCUS) avbl.
AIRPORT MANAGER: 305-876-7038
WEATHER DATA SOURCES: ASOS 119.15 (305) 870-0235. TDWR.
COMMUNICATIONS: D-ATIS ARR 119.15 (305) 869-5445 D-ATIS DEP 133.675 (305) 869-5446 UNICOM 123.0
 (R) APP CON 124.85 (270°-089°) 120.5 (090°-269°) 125.75 (270°-089°)
 TOWER 118.3 (270°-089°) 123.9 (090°-269°) GND CON 121.8 (Rwy 8L, 8R, 12, 26L, 26R) 127.5 (Rwy 09, 27, 30)
 CLNC DEL 135.35 RAMP CTL 120.35
 (R) DEP CON 119.45 (270°-089°) 125.5 (090°-269°)
 CPDLC (LOGON KUSA)
 PDC
AIRSPACE: CLASS B See VFR Terminal Area Chart

CONTINUED ON NEXT PAGE

CONTINUED FROM PRECEDING PAGE

RADIO AIDS TO NAVIGATION: NOTAM FILE MIA.

DOLPHIN (VH) (H) VORTAC 113.9 DHP Chan 86 N25°48.00' W80°20.94' 099° 3.2 NM to fld. 6/4W.

TACAN AZIMUTH unusable:

055°-065° byd 35 NM blo 3,000'

185°-195° byd 23 NM

226°-236° byd 35 NM

DME unusable:

055°-065° byd 35 NM blo 3,000'

VOR unusable:

034°-037° byd 40 NM

090°-101° byd 40 NM blo 5,500'

090°-101° byd 54 NM

102°-111° byd 40 NM

LOC/DME 109.3 I-ROY Chan 30 Rwy 08L. LOC unusable byd 30° left of course and 25° right of course. DME unusable byd 30° left of course.

ILS/DME 110.3 I-MFA Chan 40 Rwy 08R. Class IT. DME unusable byd 23° right of course. LOC unusable byd 20° right of course.

ILS/DME 110.9 I-BUL Chan 46 Rwy 09. Class IA.

ILS/DME 108.9 I-GEM Chan 26 Rwy 12. Class IT. Glideslope unusable byd 5° right of course; byd 6° left of course.

ILS/DME 109.1 I-VIN Chan 28 Rwy 26L. Class IE.

LOC/DME 109.3 I-CNV Chan 30 Rwy 26R.

ILS 109.5 I-MIA Rwy 27. Class IT.

ILS/DME 111.7 I-DCX Chan 54 Rwy 30. Class IE.

COMM/NAV/WEATHER REMARKS: PPR 3 hrs prior to all arr on the General Aviation Center (GAC) ramp 305-876-7550 ctc Ramp Ctl and upon arr on freq 131.600.