

WILMINGTON INTL (ILM)(KILM) P (AF) 3 NE UTC-5(-4DT) N34°16.27' W77°54.17'

32 B LRA Class I, ARFF Index B NOTAM FILE ILM

CHARLOTTE

H-9C, L-35B

IAP, DIAP, AD

RWY 06-24: H8016X150 (ASPH-GRVD) S-75, D-160, 2S-175,
2D-275 PCN 78 F/B/W/T HIRL

RWY 06: REIL. PAPI(P4R)—GA 3.0° TCH 57'. RVR-TR

RWY 24: MALSR. PAPI(P4L)—GA 3.0° TCH 48'. RVR-TR

RWY 17-35: H7754X150 (ASPH-GRVD) S-60, D-185, 2S-175,
2D-300 PCN 61 F/B/W/T HIRL

RWY 17: REIL. PAPI(P4L)—GA 3.0° TCH 50'. RVR-R Thld dsplcd
350'.

RWY 35: MALSR. PAPI(P4L)—GA 3.0° TCH 36'. RVR-T Thld dsplcd
400'.

RUNWAY DECLARED DISTANCE INFORMATION

RWY 06: TORA-8016 TODA-8016 ASDA-8016 LDA-8016

RWY 17: TORA-7754 TODA-7754 ASDA-6954 LDA-6604

RWY 24: TORA-8016 TODA-8016 ASDA-8016 LDA-8016

RWY 35: TORA-7754 TODA-7754 ASDA-7604 LDA-7204

SERVICE: S4 FUEL 100LL, JET A, A+ OX 1, 2, 3, 4 LGT Actv

MALSR Rwy 24 and 35; REIL Rwy 06 and 17; PAPI Rwy 06, 17, 24;
HIRL Rwy 06-24 and 17-35; and all twy lgt—CTAF. **MILITARY—FUEL**
A, A+ (C910-763-4691.) (NC-100LL)

AIRPORT REMARKS: Attended continuously. Acft taxiing from south ramp
obtain ATC clnc prior to crossing Rwy 17-35 1100-0400Z†. Traffic pattern alt 1000' AGL reciprocating engine, 1500'
AGL tbtj/jet. OHD: 5 mile initial 2500 ft AGL, break 2000 ft AGL. Tower calls drctn of break. Carrier break NA. Flight
Notification Service (ADCUS) avbl.

AIRPORT MANAGER: 910-341-4333

WEATHER DATA SOURCES: ASOS (910) 254-5254

COMMUNICATIONS: CTAF 119.9 ATIS 124.975 UNICOM 122.95

RCO 122.6 (RALEIGH RADIO)

RCO 122.1R 117.0T (RALEIGH RADIO)

Ⓡ APP/DEP CON 135.75 317.425 (344°-163°) 118.25 284.65 (164°-343°) (1100-0400Z†)

Ⓡ WASHINGTON CENTER APP/DEP CON 135.75 317.425 (0400-1100Z†)

TOWER 119.9 239.3 (1100-0400Z†) GND CON 121.9 348.6

CLEARANCE DELIVERY PHONE: For CD if una to ctc on FSS freq, ctc Washington ARTCC at 703-771-3587.

AIRSPACE: CLASS D svc 1100-0400Z†; other times CLASS E.

TRSA svc ctc APP CON within 20 NM

RADIO AIDS TO NAVIGATION: NOTAM FILE ILM.

(H) (H) VORTAC 117.0 ILM Chan 117 N34°21.10' W77°52.46' 203° 5.0 NM to fld. 29/7W.

VOR portion unusable:

051°-185°

164°-051° blo 17,500'

186°-229° blo 3,000'

230°-315° byd 5 NM blo 17,500'

316°-050° blo 8,000'

TACAN DME unusable:

015°-305° byd 30 NM blo 2,500'

TACAN AZIMUTH unusable:

129°-160° byd 30 NM blo 2,500'

WILZE NDB (LOMW) 205 GM N34°20.24' W77°48.71' 239° 6.0 NM to fld. 28/10W.

AIRLI NDB (LOMW) 281 IL N34°11.48' W77°51.98' 349° 5.1 NM to fld. 12/10W.

ILS/DME 109.95 I-GNM Chan 36(Y) Rwy 06. Class IE.

ILS 111.55 I-GMX Rwy 24. Class IIE. LOM WILZE NDB.

ILS 110.3 I-ILM Rwy 35. Class IT. LOM AIRLI NDB.

