HOMESTEAD, FLORIDA

ILS or LOC Z RWY 6

LOC I-HST	APCH CRS	Rwy ldg 11,201 TDZE 5 Arpt Elev 6
109.9	055°	

AL-494 [USAF]

HOMESTEAD ARB (KHST)

RADAR or DME required.

T * When ALS inop, increase RVR to 40, vis to ¾ mile.
** When ALS inop, increase CAT AB RVR to 55, vis to 1 mile; CAT CDE RVR to 60, vis to 1⅜ miles.

ALSF-1

MISSED APPROACH: Climb to 800 then climbing right turn to 3000 intercept HST TACAN R-180 to JOMIN and hold.

ATIS *	APP CON	TOWER	GND CON	CLNC DEL
132.275 269.9	123.8 257.675	133.45 279.55	121.75 275.8	121.75 275.8

*** Circling NA NW of Rwy 6-24.

CAUTION: Heliport and stadium 2.2 NM final Rwy 6 at Homestead ARB (stadium may be lit after dark).

Missed Approach requires use of RNAV or ATC RADAR monitoring.

HOMESTEAD Chan 19 HST

LOCALIZER 109.9 I-HST

FLATE RADAR HST 6.6

(IAF/IF) GULPE HST 16

HOLD 7000

(IAF) JOMIN HST 16 3000

HST 21

HST 16 Arc 2500 NoPT

R-180

LR-228

055° 265°K 235°

MSA HST 2.5 NM 2900 2000 230° 080°

EMERG SAFE ALT 100 NM 15,100

ELEV 6 TDZE 5

GULPE 16 21 2500 235° 055° 2500 055°

FLATE RADAR 6.6

800 3000 HST R-180 JOMIN HST 16

TACAN CODMA 1.6 2.7

GS 2.50° TCH 54 1500

5 NM 4 NM

11,201 x 300

055° 5.4 NM from FAF

HIRL Rwy 6-24

CATEGORY	A	B	C	D	E
S-ILS 6 *	205/24		200	(200-½)	
S-LOC 6 **	460/24 455 (500-½)		460/45 455 (500-⅞)		
*** C CIRCLING	460-1 454 (500-1)	500-1 494 (500-1)	520-1½ 514 (600-1½)	580-2 574 (600-2)	780-2¾ 774 (800-2¾)

FAF to MAP 5 NM					
Knots	60	90	120	150	180
Min:Sec	5:00	3:20	2:30	2:00	1:40

SE-3, 05 SEP 2024 to 03 OCT 2024
SE-3, 05 SEP 2024 to 03 OCT 2024