CAMP SPRINGS, MARYLAND

RNAV (RNP) Y RWY 01L

APCH CRS	Rwy ldg	9318
010°	TDZE	261
	Arpt Elev	280

AL-561 (USAF)

JOINT BASE ANDREWS (KADW)

RNP AR APCH. From SPISY, EDDGY: RF.

T * When ALS inop, increase RVR to 55, vis to 1 mile.
** When ALS inop, increase vis to 1 3/8 miles.

ALSF-2

MISSED APPROACH: Climb to 2500 on track 010° to EGUDE and hold.

ATIS	POTOMAC APP CON	TOWER	GND CON	CLNC DEL	CPDLC
133.675 251.05	128.0 335.5	118.4 349.0	121.8 275.8	127.55 285.475	

For uncompensated Baro-VNAV systems, Procedure NA below -15°C or above 54°C.

483

P56B P56A

HOLD 4000 2500 190° 230K 010° 4 NM

RADAR required for holding above 4000 or >230 KIAS.

EGUDE

RW01L

(IAF) EDDGY 4000

POTOMAC AFLD

010°

(FAF) FAWKS

2500 183° (12.7)

P73

2000 010° (7.1)

(IAF) SPISY

2500 231° (13.8)

OVAAL 210K

Max 210 KIAS until PREZZ

(IAF) VEEPP 2500

2500 099° (7.6)

(IF) PREZZ

2500 (9.4)

2500 (9.3)

OFICE 210K

Max 210 KIAS until PREZZ

2500 348° (14.8)

(IAF) FUNNY 8000

MSA RW01L 25 NM

2200

AUTHORIZATION REQUIRED

EMERG SAFE ALT 100 NM 6200

2500 tr 010°

EGUDE

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 72).

PREZZ

2500

FAWKS 2000

010°

RW01L

2000

GP 3.00° TCH 56

5.3 NM

CATEGORY	A	B	C	D
RNP 0.15 DA*	641/35	380	(400-⅝)	
RNP 0.30 DA**	717/45	456	(500-⅞)	

ELEV 280

TDZE 261

16L

BCN 483

9318 x 200

9756 x 150

0.3% UP

TWR 435

1L 1R

HIRL all Rwys

TDZL/CL Rwys 1L, 19R

010°

CAMP SPRINGS, MARYLAND

38°49'N - 76°52'W

JOINT BASE ANDREWS (KADW)

Amdt 2 18MAY23
TERPS

RNAV (RNP) Y RWY 01L

NE-3, 05 SEP 2024 to 03 OCT 2024