

WAAS CH 45818 W18A	APP CRS 180°	Rwy Idg 5001 TDZE 44 Apt Elev 46
--	------------------------	---

RNAV (GPS) RWY 18

HAMMOND NORTHSHORE RGNL (HDC)


RNP APCH - GPS.

Baro-VNAV and VDP NA when using Louis Armstrong New Orleans Intl altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 54°C. When local altimeter setting not received, use Louis Armstrong New Orleans Intl altimeter setting and increase LPV DA to 339 feet; increase LNAV/VNAV DA to 555 feet and all visibilities ¼ SM. Increase all MDAs 100 feet and LNAV visibility Cat C/D ¼ SM, and Circling visibility Cat C/D ½ SM. For inop ALS when using Louis Armstrong New Orleans Intl altimeter increase LPV all Cats visibility to ¾ SM; LNAV/VNAV all Cats visibility to 1¾ SM and LNAV Cats C/D visibility to 1¾ SM. For inop ALS increase LNAV/VNAV all Cats visibility to 1¼ SM and LNAV Cat C/D visibility to 1¾ SM.

MALSR

MISSED APPROACH:
Climb to 2200 direct IYRON and hold.

ATIS 118.325	NEW ORLEANS APP CON 119.3 350.35	HAMMOND TOWER ★ 120.575 (CTAF) 0	GND CON 119.85	CLNC DEL 119.3 (When twr closed)
------------------------	--	---	--------------------------	---



BARUN		SUGVE		TUALA		RW18	
1800		1800		1800		660	
GP 3.00°		1800		1.1 NM to RW18		RW18	
TCH 52		9.4 NM		3.5 NM		0.7 NM	
CATEGORY		A		B		C	
LPV DA		250-½		206 (300-½)			
LNAV/VNAV DA		466-¾		422 (500-¾)			
LNAV MDA		460-½		416 (500-½)		460-¾	
CIRCLING		500-1		454 (500-1)		620-1½	
						574 (600-1½)	
						920-2¾	
						874 (900-2¾)	

ELEV 46

TDZE 44

2200

IYRON

81

180°

5001 X 100

6502 X 100

36

96

TWR 131

31

13

REIL Rwy 13, 31 and 36 **0**
MIRL Rwy 13-31 and 18-36 **0**