

(DAWNN1.DAWNN) 23334
DAWNN ONE DEPARTURE


AL-6452 (FAA)

INDIANAPOLIS RGNL (MQJ)
 INDIANAPOLIS, INDIANA

**TOP ALTITUDE:
 ASSIGNED BY ATC**

AWOS-3PT
 124.175
 CLNC DEL
 119.25
 INDIANAPOLIS DEP CON
 127.15 317.8

BRICKYARD
 116.3 VHP
 Chan 110



R-098
 TERRE HAUTE
 115.3 TTH
 Chan 100


R-174
 (28)
 SNEVA
 RADAR

TAKEOFF MINIMUMS:

Rwys 7, 16, 25: Standard.
 Rwy 34: 300-1 or standard with minimum climb
 of 347' per NM to 1100.

R-113
 HOOSIER
 110.2 OOM
 Chan 39

(47)
 FOYTT
 RADAR



6000
 174°
 (75)
 DAWNN
 10000
 (For LOUISVILLE Transition)

10000
 *3000
 131°
 (41)
 R-311

LOUISVILLE
 114.8 IU
 Chan 95

6000
 *2300
 182°
 (40)
 R-002
 MYSTIC
 108.2 MYS

- NOTE: RADAR required.
- NOTE: Select appropriate localizer/DME frequency/channel prior to departure.
- NOTE: Turbojets accelerate to 250K until reaching 10000, if unable advise ATC.
- NOTE: Assigned to aircraft with a requested altitude of 11000 or above.

(NARRATIVE ON FOLLOWING PAGE)

NOTE: Chart not to scale.

EC-2, 03 OCT 2024 to 31 OCT 2024

EC-2, 03 OCT 2024 to 31 OCT 2024