

SKYLANE (See EVANSVILLE on page 104)

SMITH FLD (See FORT WAYNE on page 106)

SNOW LAKE SPB (See JAMESTOWN on page 121)

SOUTH BEND INTL (SBN)(KSBN) 3 NW UTC-5(-4DT) N41°42.49' W86°19.04'

CHICAGO
H-5E, IAF, L-281
IAF, AD

798 B Class I, ARFF Index B NOTAM FILE SBN

RWY 09R-27L: H8412X150 (ASPH-GRVD) S-120, D-193, 2S-175,
2D-313 PCR 450 F/B/X/T HIRL

RWY 09R: MALSF. PAPI(P4L)—GA 3.0° TCH 56'. RVR-T Tree.
0.5% down.

RWY 27L: MALS. PAPI(P4L)—GA 3.0° TCH 55'. RVR-TR Tree.

RWY 18-36: H7101X150 (ASPH-GRVD) S-118, D-186, 2S-175,
2D-326 PCR 410 F/B/X/U MIRL 0.5% up N

RWY 18: PAPI(P4L)—GA 3.0° TCH 52'. Tree.

RWY 36: PAPI(P4L)—GA 3.0° TCH 53'. Tree.

RWY 09L-27R: H4300X75 (ASPH) S-32.5, D-49 PCR 430 F/B/X/T
MIRL

RWY 09L: PAPI(P2L)—GA 3.0° TCH 44'. Tree.

RWY 27R: PAPI(P2L)—GA 3.0° TCH 46'. Tree.

RUNWAY DECLARED DISTANCE INFORMATION

RWY 09L:TORA-4300 TODA-4300 ASDA-4300 LDA-4300

RWY 09R:TORA-8412 TODA-8412 ASDA-8412 LDA-8412

RWY 18: TORA-7101 TODA-7101 ASDA-7101 LDA-7101

RWY 27L:TORA-8412 TODA-8412 ASDA-8412 LDA-8412

RWY 27R:TORA-4300 TODA-4300 ASDA-4300 LDA-4300

RWY 36: TORA-7101 TODA-7101 ASDA-7101 LDA-7101

SERVICE: S4 FUEL 100LL, JET A OX1, 2, 3, 4 LGT When ATCT clsd actvt & incr instst MALSF Rwy 09R; MALS Rwy 27L; HIRL Rwy 09R-27L; MIRL Rwy 18-36; twy exc Twy J, J1, J2—CTAF.

AIRPORT REMARKS: Attended continuously. Birds on and invof arpt. Rwy 09L-27R CLOSED when twr clsd. Rwy end 27R: be alert durg right base, high tension wires AER. Line of sight btn rwy insts rstrd. Acr ramp rstrd to sked coml and wingspan gr than 100'; all otr 24 hr PPR. Rwy 09L-27R not avbl to acr ops more than 9 pax seats or unskd acr at least 31 pax seats. Wt rstrd 45,000 single & 60,000 dual. Twys J, J1, J2 & T not avbl to acr ops with more than 9 pax seats or unskd acr at least 31 pax seats. Twy B btn B1 & B2 rstrd to acft no lgr than B757 or wingspan lgr than 125 ft. Twy J, J1 and J2 clsd when twr clsd. User fee arpt: 24 hr PPR for Customs and Border Protection — 574-232-9650; wkend svc call bfr 2100Z±. Index C available upon req.

AIRPORT MANAGER: 574-282-4590

WEATHER DATA SOURCES: ASOS 120.675 (574) 251-2652.

COMMUNICATIONS: CTAF 135.675 ATIS 120.675

Ⓡ **SOUTH BEND APP/DEP CON** 118.55 (270°-099°) 132.05 (100°-269°) (1030-0500Z± Sun-Fri, 1030-0445Z± Sat.), other times ctc

Ⓡ **CHICAGO CENTER APP/DEP CON** 118.55

SOUTH BEND TOWER 135.675 (1030-0500Z± Sun-Fri, 1030-0445Z± Sat.) **GND CON** 121.7 **CLNC DEL** 121.9

CLEARANCE DELIVERY PHONE: For CD ctc South Bend Apch at 574-251-2609. When South Bend Apch clsd, for CD ctc Chicago ARTCC at 630-906-8921.

AIRSPACE: CLASS C svc ctc **APP CON** svc 1030-0500Z± Sun-Fri 1030-0445Z± Sat; other times CLASS E.

RADIO AIDS TO NAVIGATION: NOTAM FILE LAN.

GIPPER (H) (H) VORTACW 115.4 GIJ Chan 101 N41°46.12' W86°19.11' 179° 3.6 NM to fld. 804/OE.

TACAN AZIMUTH unusable:

245°-255°

276°-306° byd 25 NM blo 3,000'

307°-312° byd 25 NM blo 4,500'

313°-331° byd 25 NM blo 3,000'

DME unusable:

276°-306° byd 25 NM blo 3,000'

307°-312° byd 25 NM blo 4,500'


313°-331° byd 25 NM blo 3,000'

MISHA NDB (LOMW) 341 SB N41°42.34' W86°13.14' 277° 4.4 NM to fld. 750/5W. NOTAM FILE SBN.

ILS 109.3 I-UXW Rwy 09R. Unmonitored when ATCT clsd. LOC unusable byd 25° left and right of course.

ILS 109.3 I-SBN Rwy 27L. Class IIE. LOM MISHA NDB. OM unmonitored. Unmonitored when ATCT clsd.

COMM/NAV/WEATHER REMARKS: For fuel & svcs - 122.95 or 131.7.



STARKE CO (See KNOX on page 124)