ILS or LOC RWY 35

MANCHESTER BOSTON RGNL (MHT)

LOC/DME I-MHT	APP CRS	Rwy Idg	7650
109.1	352°	TDZE	265
Chan 28		Apt Elev	266

From SHOWZ: RNAV 1-DME/DME/IRU or GPS required.
DME or RADAR required.

Rwy 35 helicopter visibility reduction below RVR 4000 NA.
For inop ALS, increase S-LOC 35 Cats A/B visibility to RVR 5500.

ALSF-2

MISSED APPROACH: Climb to 4000 direct CON VOR/DME and hold.

ATIS	BOSTON APP CON	MANCHESTER TOWER	GND CON	CLNC DEL
119.55	124.9 269.075	121.3 239.025	121.9	135.9

MSA MHT 25 NM
3700

1049
1523
530± 985
1215
620± 543
386
IM
547 463± 625±
MM
XOHWI
I-MHT 3.5
MNTIN
I-MHT 5.6
(IF)
YOULL
I-MHT 8.7
1600
352°
(3)
2500
352°
(3.8)
(IAF)
SHOWZ
5000 210K
3000
053°
(6.2)
2500
022° (3.5)
ELEEE
(IAF)
PELAN
I-MHT 12.4
3000
087°
(5.3)
IHOBB
172°

LOCALIZER 109.1
I-MHT
Chan 28

MISSED APCH FIX
R-330 150° 330°
CONCORD
CON
112.9
Chan 76

ELEV 266 D TDZE 265



REIL Rwys 6 and 24
TDZ/CL Rwy 17 and 35
HIRL Rwys 6-24 and 17-35

4000	CON

VGSI and ILS glidepath not coincident (VGSI Angle 3.00/TCH 68).
Use I-MHT DME when on the localizer course.

*LOC only.



CATEGORY	A	B	C	D
S-ILS 35	465/18 200 (200-½)			
S-LOC 35	720/40 455 (500-¾)		720/45 455 (500-⅞)	

NE-1, 31 OCT 2024 to 28 NOV 2024
NE-1, 31 OCT 2024 to 28 NOV 2024