APP CRS	Rwy Idg	8207
219°	TDZE	11
	Apt Elev	17

RNAV (RNP) Y RWY 22L

NEWARK LIBERTY INTL (EWR)

RNP AR APCH - GPS.

For uncompensated Baro-VNAV systems, procedure NA below -13°C or above 54°C.

ALSF-2

MISSED APPROACH: Climb to 600 then climbing right turn to 3000 direct KILMA and hold.

D-ATIS	NEWARK APP CON	NEWARK TOWER	GND CON	CLNC DEL	CPDLC
115.7 134.825	128.55 379.9	118.3 257.6	121.8	118.85	

NE-2, 31 OCT 2024 to 28 NOV 2024

RADAR REQUIRED

(IF) HEVNU

3000 219° (4.1)

1048

2500 219° (1.8) CUBMO 3000

(FAF) OSUSE

968 675

800± 219° (7.7) 1649

503 597 333 849± 1806

357 RW22L 460

312 634±

335± 727 693

515

MSA RW22L 25 NM 2900

KILMA

072° 252° 4 NM

ELEV 17 D TDZE 11

219°

22L 22R 29

6726 X 150

TWR 348

11000 X 150 10000 X 150

4L 4R

TDZ/CL Rwys 4L, 4R, 11, 22L, 22R, and 29

REIL Rwys 11, 22R, and 29

HIRL Rwys 4L-22R, 4R-22L, and 11-29

600	3000	KILMA

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 60).

OSUSE 2500 CUBMO HEVNU 219° 3000 3000 RW22L 2500 GP 3.00° TCH 43

7.7 NM 1.8 NM 4.1 NM

CATEGORY	A	B	C	D
RNP 0.30 DA	462/50	451 (500-1)		

AUTHORIZATION REQUIRED