ILS Z or LOC Z RWY 23

ADAK (ADK) (PADK)

LOC I-BER	APP CRS	Rwy Idg	6190
108.9	234°	TDZE	18
		Apt Elev	20

ADF and DME required.

Circling NA at night. Circling NA northwest of Rwy 5-23. Rwy 23 helicopter visibility reduction below ¾ SM NA. DME from ADK NDB. Simultaneous reception of I-BER and ADK DME required. Cat E for USAF/USN use only.

MALS

MISSED APPROACH: Climb to 5400 direct ADK NDB/DME and on the 241° bearing from ADK NDB/DME to COMAT/ADK 10 DME and left turn direct ADK NDB/DME and hold.Missed approach requires minimum climb of 409 feet per NM to 2700; if unable to meet climb gradient, see ILS Y or LOC Y RWY 23.

AWOS-3P	ANCHORAGE CENTER	CTAF
134.5	126.4 254.3	122.9 L







CATEGORY	A	B	C	D	E
S-ILS 23	309/50 291 (300-1)				
S-LOC 23	480/55 462 (500-1)		480-1⅜ 462 (500-1⅜)		
C CIRCLING	720-1 700 (700-1)		1060-3 1040 (1100-3)	2400-3 2380 (2400-3)	2440-3 2420 (2500-3)

AK, 31 OCT 2024 to 26 DEC 2024
AK, 31 OCT 2024 to 26 DEC 2024