RNAV (RNP) Z RWY 6L

GUAM INTL (GUM)(PGUM)

APP CRS	Rwy Idg	11014
063°	TDZE	256
	Apt Elev	305

RNP AR APCH - GPS.

For uncompensated Baro-VNAV systems, procedure NA below 19°C or above 48°C. For inop ALS, increase RNP *0.30 all Cats visibility to ¾ SM and RNP 0.30 all Cats visibility to 1⅛ SM.
*Missed approach requires a minimum climb of 276 feet per NM to 1400.

MALSR

MISSED APPROACH: Climb to 3000 via track 063° to WABOX and hold.

ATIS	GUAM CERAP	AGANA TOWER	GND CON	CLNC DEL
119.0	119.8 269.0	118.1 340.2	121.9 336.4	121.9

WUVEN 15900
Procedure NA for arrivals at WUVEN via A597 northwest bound.
3000 166° (35.9)
Procedure NA for arrivals at PULEE via G467 R596 westbound.
(IAF) PULEE 13300
3000 102° (32.6)
(IAF) RASPE 4500 210K
3000 153° (5)
(IF) OBALE
2000 063° (7)
(FAF) ADEDE
724 063° (5.3)
1190
RW06L
412
812
063° (13.7)
412
MISSED APCH FIX
4 NM
063°
243°
WABOX
MSA RW06L 25 NM
2600
1332
3000 333° (10)
(IAF) BURLE 6100
3000 337° (28.6)
Procedure NA for arrivals at ASADE via B586 southeast bound.
ASADE 15100

ELEV 305 D TDZE 256

341±
2.4R
2.4L
0.5% UP
0.7% DOWN
12014 X 150
10014 X 150
0.8% UP
0.6% DOWN
TWR 352
554
270±
063°

Procedure Turn NA
OBALE
VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 73)
3000
tr 063°
WABOX
3000
063°
ADEDE
2000
2000
GP 3.00°
TCH 50
7 NM
5.3 NM

CATEGORY	A	B	C	D
RNP 0.30* DA	514-½ 258 (300-½)			
RNP 0.30 DA	656- 5/8 400 (400- 5/8)			

AUTHORIZATION REQUIRED

HIRL all Rwys

PAC, 31 OCT 2024 to 26 DEC 2024
PAC, 31 OCT 2024 to 26 DEC 2024