

OZARK EIGHT DEPARTURE


AL-5316 (FAA)

ST LOUIS DOWNTOWN (CPS)
CAHOKIA/ST. LOUIS, ILLINOIS

ATIS 121.45
 CLNC DEL 118.275
 121.8 (when tower closed)
 GND CON 121.8
 DOWNTOWN TOWER* 119.925 379.3
 ST LOUIS DEP CON 123.7 371.875



ST. LOUIS
 117.4 STL
 Chan 121



NOTE: Chart not to scale.

EC-3, 31 OCT 2024 to 28 NOV 2024

TOP ALTITUDE:
 2500

HALLSVILLE
 114.2 HLV
 Chan 89

8000
 *2500
 281°
 (46)

8000
 *2100
 281°
 (32)

NOTE: DME and RADAR required.

TAKEOFF MINIMUMS

- Rwys 12L/R, 23, 30R: Standard.
- Rwy 5: 200-1/4 or standard with minimum climb of 343' per NM to 700.
- Rwy 30L: 400-2 1/2 or standard with minimum climb of 220' per NM to 900, or alternatively, with standard takeoff minimums and a normal 200' per NM climb gradient, takeoff must occur no later than 2100' prior to DER.

(CONTINUED ON FOLLOWING PAGE)

EC-3, 31 OCT 2024 to 28 NOV 2024

OZARK EIGHT DEPARTURE

CAHOKIA/ST. LOUIS, ILLINOIS
ST LOUIS DOWNTOWN (CPS)