

RADAR MINS

22139

N1

RADAR INSTRUMENT APPROACH MINIMUMS

LEMOORE NAS (REEVES FIELD)(KNLC), Leemore, CA Amdt 8

19MAY22 (22139) (USN)

ELEV 228

RADAR - (E) 125.95 270.8x 314.0x 317.575x 322.45x 323.15x 336.4x 346.375x 348.75x 353.55x
363.7x 370.875x 377.075x **T**

	<u>RWY</u>	<u>GS/TCH/RPI</u>	<u>CAT</u>	<u>DH/ MDA-VIS</u>	<u>HAT/ HATH/ HAA</u>	<u>CEIL-VIS</u>
PAR ^{1,4}	32L ^{2,6}	3.0°/40/743	ABCDE	327 -¼	100	(100-¼)
	14L	3.0°/54/983	ABCDE	319 -½	100	(100-½)
	14R ⁵	3.0°/52/977	ABCDE	328 -½	100	(100-½)
	32R ⁵	3.0°/46/870	ABCDE	321 -½	100	(100-½)
ASR ⁴	32L ^{3,7}		AB	580 -½	353	(400-½)
			CDE	580 -⅝	353	(400-⅝)
	14L		ABCDE	560 -1	341	(400-1)
	14R ⁵		AB	680 -1	452	(500-1)
			CDE	680 -1⅙	452	(500-1⅙)
	32R ⁵		AB	760 -1	539	(600-1)
CDE			760 -1½	539	(600-1½)	
CIR ⁸	14L, 14R, 32L		AB	680 -1	452	(500-1)
			C	700 -1½	472	(500-1½)
			DE	780 -2	552	(600-2)
	32R		AB	760 -1	532	(600-1)
			C	760 -1½	532	(600-1½)
			DE	780 -2	552	(600-2)

¹No-NOTAM MP: PAR-Rwy 14R-32L 1600-2400Z++ Mon, Rwy 14L-32R 1600-2400Z++ Wed.

²When ALS inop, increase vis to ½ mile.

³When ALS inop, increase vis to 1 mile.

⁴Simultaneous approaches authorized.

⁵Pattern at 2800 ft.

⁶Caution: WCH group 4: 15 ft less than required 20 ft.

⁷Step Down Fix at 3 NM from thld, 1100 min.

⁸Circling authorized only from ASR.

31 OCT 2024 to 28 NOV 2024

31 OCT 2024 to 28 NOV 2024

SW-2

RADAR INSTRUMENT APPROACH MINIMUMS

RADAR MINS

22139

N1