

WAAS CH 58125 W25A	APP CRS 253°	Rwy Idg TDZE Apt Elev	6004 113 113
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 25


EXEC (ORL)

RNP APCH - GPS

⚠ Circling Rwy 31 NA at night. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below 2°C or above 54°C. In minimum visibility conditions, bright lights on highway ½ mile south of airport may be mistaken for runway lights.

MISSED APPROACH: Climb to 600 then climbing right turn to 1700 direct FTEEN and hold.



ATIS 127.25	ORLANDO APP CON 124.8 351.9	EXECUTIVE TOWER * 118.7 (CTAF) 0 239.0	GND CON 121.4 239.0	CLNC DEL 128.45	UNICOM 122.95
-----------------------	---------------------------------------	---	-------------------------------	---------------------------	-------------------------



SE-3, 28 NOV 2024 to 26 DEC 2024

SE-3, 28 NOV 2024 to 26 DEC 2024

ELEV 113	D	TDZE 113
----------	----------	----------



CATEGORY	A	B	C	D
LPV DA		313-¾	200 (200-¾)	
LNAV/VNAV DA		390-⅞	277 (300-⅞)	
LNAV MDA	500-1	387 (400-1)	500-1¼	387 (400-1¼)
CIRCLING	580-1 467 (500-1)	680-1 567 (600-1)	860-2¼ 747 (800-2¼)	860-2½ 747 (800-2½)