

WAAS CH 70520 W28A	APP CRS 277°	Rwy Idg TDZE Apt Elev	6501 26 26
--	------------------------	-----------------------------	---------------------------------------


RNAV (GPS) RWY 28

TAMPA INTL (TPA)


⚠ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -1 5°C (5°F) or above 43°C (109°F). DME/DME RNP-0.3 NA. Helicopter visibility reduction below ¾ SM NA.

MISSED APPROACH: Climb to 2000 direct POLY and hold.


D-ATIS ARR 126.45 DEP 128.475	TAMPA APP CON 118.5 307.175	TAMPA TOWER 119.5 269.4	GND CON 121.7 269.4	CLNC DEL 133.6	CPDLC
---	---------------------------------------	-----------------------------------	-------------------------------	--------------------------	-------



ELEV 26	D	TDZE 26
---------	----------	---------



REIL Rwy 1R TDZ/CL Rwys 1L and 19L HIRL Rwys 1L-19R, 1R-19L, and 10-28
--



CATEGORY	A	B	C	D
LPV DA		389-1 1/8	363 (400-1 1/8)	
LNAV/VNAV DA		468-1 1/2	442 (500-1 1/2)	
LNAV MDA	520-1	494 (500-1)	520-1 3/8	494 (500-1 3/8)
C CIRCLING	560-1	534 (600-1)	680-1 3/4 654 (700-1 3/4)	980-3 954 (1000-3)