LOC I-APN	APP CRS	Rwy Idg	9001
109.7	007°	TDZE	685
		Apt Elev	690

ILS or LOC RWY 1
ALPENA COUNTY RGNL (APN)

ADF required.

For inop ALS, increase S-LOC 1 Cat C/D visibility to 1⅝ SM.

MALSR

MISSED APPROACH: Climb to 1100 then climbing left turn to 2800 direct AP LOM and hold.

ATIS	ALPENA APP CON ★	ALPENA TOWER ★	GND CON	UNICOM
120.675 327.05	128.425 379.3	121.35 (CTAF) L 318.1	121.9 275.8	122.95

ALTERNATE MISSED APCH FIX

R-355 175° 355°

ALPENA APN 116.5 Chan 112

LOCALIZER 109.7 I-APN

ALPENA 116.5 APN Chan 112

1140 775 965 1409 799± 907

2800 to LOM 188° (7.3)

HOMSU APN 2.8

LOM/IAF FELPS 206 AP APN 7.3

187°

(IF) YARLU APN 13.3

007° (6) 2800

1648

2800 to YARLU 090° (3.9) and 007° (2.7)

142° 322°

(IAF) AILES APN 17

187°

MSA APN 25 NM 180° 3500 090° 2700

ELEV 690 D TDZE 685

HIRL Rwy 1-19 L

MIRL Rwy 7-25 L

REIL Rwys 7, 19 and 25 L

6L TWR 768 5028 X 100 25 9001 X 150 1 007°

1100	2800	AP

*LOC only.

FELPS LOM APN 7.3

Remain within 10 NM

187° 2761 007° 2800

HOMSU APN 2.8

APN 1.1

1260* 2800

GS 3.00° TCH 52

1.7 NM 4.6 NM

CATEGORY	A	B	C	D
S-ILS 1	885-½ 200 (200-½)			
S-LOC 1	1260-½ 575 (600-½)		1260-1¼ 575 (600-1¼)	

FAF to MAP 6.3 NM

Knots	60	90	120	150	180
Min:Sec	6:18	4:12	3:09	2:31	2:06

HOMSU FIX MINIMUMS

S-LOC 1	1140-½ 455 (500-½)

EC-1, 28 NOV 2024 to 26 DEC 2024
EC-1, 28 NOV 2024 to 26 DEC 2024