

# LINDBERGH EIGHT DEPARTURE

AL-5316 (FAA)

ST LOUIS DOWNTOWN (CPS)  
CAHOKIA/ST. LOUIS, ILLINOIS

ATIS  
121.45  
CLNC DEL  
118.275  
CLNC DEL  
121.8 (when twr closed)  
GND CON  
121.8  
DOWNTOWN TOWER\*  
119.925 379.3  
ST LOUIS DEP CON  
123.7 371.875

**TOP ALTITUDE:  
2500**

ST. LOUIS  
117.4 STL ...  
Chan 121

VICHY  
117.7 VIH ...  
Chan 124

FARMINGTON  
115.7 FAM ...  
Chan 104

LITTLE ROCK  
113.9 LIT ...  
Chan 86

WALNUT RIDGE  
114.5 ARG ...  
Chan 92

### TAKEOFF MINIMUMS

Rwys 12L/R, 23, 30R: Standard.  
Rwy 5: 200-1¼ or standard with minimum climb of 343' per NM to 700.  
Rwy 30L: 400-2½ or standard with minimum climb of 220' per NM to 900, or alternatively, with standard takeoff minimums and a normal 200' per NM climb gradient, takeoff must occur no later than 2100' prior to DER.

NOTE: DME and RADAR required.

(CONTINUED ON FOLLOWING PAGE)

NOTE: Chart not to scale.

# LINDBERGH EIGHT DEPARTURE

