TOP ALTITUDE:
RWYS 31L/R: 5000
RWYS 17C/R, 18L/R, 35L/C, 36L/R: 10000
RNAV 1 - DME/DME/IRU or GPS.
RADAR required.
NOTE: For use by turbojet aircraft only.
NOTE: Non-RNAV capable props: file and expect DALLAS or GARLAND DEPARTURE.
NOTE: RNAV capable props: file and expect the KUSSO RNAV DEPARTURE.
LONE STAR DEP CON
118.55 290.35
D-ATIS DEP
135.925
CLNC DEL
128.25
CPDLC
GND CON
121.65 121.8 (EAST)
121.85 (WEST)
DFW TOWER
126.55 127.5 (EAST)
124.15 134.9 (WEST)
CUZEN
5000
FEZTR
7000
SWYFT
ZERLU
TRRCH
CORTS
JGIRL
5000
SPERA
SWDIA
JAYXX
ZACHH
TRYTN
LOOSE
FORCK
LYING
JJANE
MRSSH
HANUH
THHOR
082° (4)
095° (6)
108° (27)
090° (26)
084° (5)
107° (3)
356°
004°
090°
176°
157°
155°
145°
143°
1120
N
10000 *240° 990 (26)
10000 *240° 990 (18)
10000 *240° 990 (12)
TAKEOFF MINIMUMS
Rwys 31L/R: Standard.
Rwys 17C/R, 18L/R, 35L/C, 36L/R: Standard with minimum climb of 500' per NM to 1120.
(CONTINUED ON FOLLOWING PAGE)
NOTE: Chart not to scale.