





WAAS CH 99644 W18A	APP CRS 180°	Rwy Idg TDZE Apt Elev	6001 1316 1316
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 18

MONETT RGNL (HFJ)

RNP APCH - GPS.			MISSED APPROACH: Climb to 3100 direct STERL and hold.
▼ Baro-VNAV and VDP NA when using Joplin altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C or above 54°C. When local altimeter setting not received, use Joplin altimeter setting; increase LPV DA to 1678 feet and all visibilities ¼ SM; increase LNAV/VNAV DA to 1742 feet and all visibilities ⅓ SM; increase all MDAs 120 feet and LNAV visibility Cat C/D ½ SM, and Circling visibility Cat C/D ½ SM.			
AWOS-3 118.275	SPRINGFIELD APP CON 124.95 318.2	CLNC DEL 121.85	UNICOM 123.075 (CTAF) 📻



3100	STERL	SOFWR	PHENM	4 NM Holding Pattern
KNOXX 1.9 NM to RW18		3000	180°	360° → 4000 ← 180° 3000
RW18 1.1 NM to RW18		1960	3000	GP 3.00° TCH 43
1.1 NM		0.8	3.3 NM	6 NM
CATEGORY	A	B	C	D
LPV DA	1566-¾		250 (300-¾)	
LNAV/VNAV DA	1630-⅞		314 (400-⅞)	
LNAV MDA	1700-1	384 (400-1)	1700-1⅛	384 (400-1⅛)
C CIRCLING	1760-1 444 (500-1)	1900-1 584 (600-1)	1900-1½ 584 (600-1½)	2060-2½ 744 (800-2½)

NC-3, 28 NOV 2024 to 26 DEC 2024

NC-3, 28 NOV 2024 to 26 DEC 2024