

**NAPLES MUNI** (APF)(KAPF) 2 NE UTC-5(-4DT) N26°09.15' W81°46.54'

8 B Class I, ARFF Index A NOTAM FILE APF

**RWY 05-23:** H6600X150 (ASPH-GRVD) D-75 PCR 210 F/B/X/T

MIRL

**RWY 05:** REIL. PAPI(P4R)—GA 3.5° TCH 31'. Thld dsplcd 800'. Road. Rgt tfc.

**RWY 23:** REIL. PAPI(P4L)—GA 3.0° TCH 42'. Thld dsplcd 799'. Fence.

**RWY 14-32:** H5001X100 (ASPH-GRVD) S-75, D-75

PCR 320 F/B/X/T MIRL

**RWY 14:** REIL. PAPI(P4L)—GA 3.5° TCH 41'. Thld dsplcd 128'. Trees. Rgt tfc.

**RWY 32:** REIL. PAPI(P4L)—GA 3.0° TCH 40'. Thld dsplcd 451'. Trees.

**RWY NE-SW:** 1850X100 (TURF)

**RUNWAY DECLARED DISTANCE INFORMATION**

**RWY 05:** TORA-5800 TODA-5800 ASDA-5800 LDA-5000

**RWY 14:** TORA-5001 TODA-5001 ASDA-4550 LDA-4422

**RWY 23:** TORA-5800 TODA-5800 ASDA-5800 LDA-5000

**RWY 32:** TORA-5001 TODA-5001 ASDA-4873 LDA-4422

**SERVICE:** S4 FUEL 100LL, JET A, A+, UL94 OX 3, 4 LGT When ATCT clsd actvt REIL Rwy 05, 14, 23 and 32; PAPI Rwy 14 and 32; MIRL Rwy 05-23 and 14-32—CTAF.

**NOISE:** Extmy noise sensitive area; use noise abatement procs. Voluntary restrictions exist for all acft ops 0300-1200Z†.

**AIRPORT REMARKS:** Attended 1100-0300Z†. Full svc fuel not avbl dly 0130-1030Z†. Clsd to acft exceeding 75,000 lbs max GWT dual gear indcd on acft orgp cert issued by manufacturer. Runups NA 0300-1200Z†; Twy A runup pads for Rwy 05-23 piston acft only; jet acft runup area Twy C btw Twy C3 and Twy D PPR—ATCT. Twy C fm C1 to ER Rwy 32 not visible fm ATCT. Rwy NE-SW mkd with pavers and PVC pipes. Rwy 23 dsngd calm wind rwy for arrs 0300-1100Z†. Rwy 5 dsngd calm wind rwy for depts 0300-1100Z†. APF GA aprn ctn obst lgt poles. PPR US customs svc Mon-Sun 1530-0000Z† PPR-239-430-9321. US Customs and Border Protection User Fee Arrt.

**AIRPORT MANAGER:** 239-643-0733

**WEATHER DATA SOURCES:** ASOS 134.225 (239) 643-9886.

**COMMUNICATIONS:** CTAF 128.5 ATIS 134.225 (239) 643-5230

RCO 122.5 (MIAMI RADIO)

Ⓡ **FORT MYERS APP/DEP CON** 124.125 (1100-0500Z†)

Ⓡ **MIAMI CENTER APP/DEP CON** 134.75 (0500-1100Z†)

**TOWER** 128.5 (1100-0300Z†) **GND CON** 121.6 **CLNC DEL** 118.0

**CLNC DEL** 124.125 (When twr clsd, monitored by Fort Myers App Con)

**CLEARANCE DELIVERY PHONE:** For CD if una to ctc on FSS freq, ctc Ft Myers Apch at 239-416-1026, when Apch clsd ctc Miami ARTCC at 305-716-1731.

**AIRSPACE:** CLASS D svc 1100-0300Z†; other times CLASS G.

**RADIO AIDS TO NAVIGATION:** NOTAM FILE APF.

CYPRESS (T) (T) **VORW/DME** 108.6 CYY Chan 23 N26°09.21' W81°46.69' at fld. 9/3W.


DME unusable:

215°-315°

VOR unusable:

078°-139° blo 10,000'

**COMM/NAV/WEATHER REMARKS:** UNICOM freq: For FBO svc ctc—128.825.



**MIAMI**  
H-8H, L-21D, 23B  
IAP, AD

## NAVARRÉ

**FORT WALTON BEACH** (1J9) 2 E UTC-6(-5DT) N30°24.38' W86°49.75'

**NEW ORLEANS**

22 NOTAM FILE GNV

**RWY 18-36:** 2100X65 (TURF) 1.0% up N

**RWY 18:** Bldg.

**RWY 36:** Brush.

**AIRPORT REMARKS:** Attended 1600Z†-dusk. Hel more than 2500 lbs na. Dep Rwy 18; arr Rwy 36. Rwy slopes to 2 ft at S end. Unlgt'd brush, trees, prkg and bldg 65-125 ft W of cntr'n full len. Rwy 18-36 bare spots soft and sandy S of mid point. Rwy 18-36 white cones.

**AIRPORT MANAGER:** (850) 244-1313

**COMMUNICATIONS:** CTAF/UNICOM 122.7

**CLEARANCE DELIVERY PHONE:** For CD ctc Egl'n Apch 850-882-9152 or 850-882-9151.

**NEW HIBISCUS AIRPARK** (See VERO BEACH on page 179)