

**CHARLESTON AFB/INTL** (CHS)(KCHS) MIL/CIV AF 9 NW UTC-5(-4DT) N32°53.92' W80°02.43' **CHARLOTTE**  
 46 B TPA—See Remarks LRA Class I, ARFF Index C NOTAM FILE CHS **H-9C, 12G, L-241**  
**IAP, AD**

**RWY 15-33:** H9001X150 (CONC-GRVD) PCN 73 R/B/W/T HIRL CL  
**RWY 15:** ALSF2. TDZL. PAPI(P4L)—GA 3.0° TCH 50'. RVR-TMR  
**RWY 33:** MALSR. PAPI(P4L)—GA 3.0° TCH 59'. RVR-TMR  
**RWY 03-21:** H7000X150 (CONC-GRVD) PCN 71 R/B/W/T HIRL 0.3% up NE  
**RWY 03:** REIL. PAPI(P4L)—GA 3.0° TCH 50'.  
**RWY 21:** REIL. PAPI(P4L)—GA 3.0° TCH 50'.

**LAND AND HOLD—SHORT OPERATIONS**

LDG RWY	HOLD—SHORT POINT	AVBL LDG DIST
RWY 03	15-33	5400
RWY 15	03-21	5450
RWY 33	03-21	2650

**ARRESTING GEAR/SYSTEM**

**RWY 15** TYPE-H BAK-12A(B) (1260') TYPE-H BAK-12A(B) (1460') **RWY 33**

**SERVICE:** S4 FUEL 100, JET A1+ **OX 1** LGT PAPI's set for Hgt Gp 3 acft. Rot Bcn not vis fr NW. **RWY 15** ALSF-2 also opr as SSALR dur VMC. **MILITARY—JASU** 8(MD-3M) 2(MA-1A) (M32A-60) (M32A-60) FUEL A++(Mil), 100, A1+ **FLUID** SOAP - Routine SOAP samples not avbl; SP PRESAIR LHOX LOX OIL Non-detergent oil not avbl for piston acft. O-128-133-148(Mil) **TRAN ALERT** Mil acft for FBO prk/svc rqr PPR C843-746-7600. Mil provides no security and no acft svc at FBO's and coml trml.

**NOISE:** NS ABTMT: Practice circle apch prohibited 0200-1100Z.

**AIRPORT REMARKS:** Attended continuously. Migratory bird season Phase II Apr 1-15 Apr and 1 Aug-Nov 30. **Rwy 03-21** CLOSED 2nd Tue ea month 1330-2200Z. **Rwy 15-33** CLOSED last Tue of ea month 1330-2200Z. All acft use upper antenna until airborne. Ints heavy mil jets and other miscellaneous acft executing numerous cargo and personnel DRRs, high speed low-level formation flts and miscellaneous air to gnd ops. No stu solo touch and go ldg allowed. PPR for parking of general aviation acft on terminal ramp ctc 843-767-1100. Parking on terminal apron rstd to coml air carrier and acft for cstmns clnc by prior arrangement only. Flight Notification Service (ADCCU) avbl.

**MILITARY REMARKS:** See FLIP AP/1 Supplementary Arpt Remark. **RSTD** Afld Mgmt DSN 673-3024/6, C843-963-3024/6. Tran acft for mil ramp Follow-Me rqr. All acft must ctc Palmetto OPS prior to entering mil ramp for parking assignment. PPR, exc AIREVAC, SAM and AMC GDSSII msn, for number and lcl trng flt tran alert support ctc Afld Mgmt DSN 673-3024/6, C843-963-3024/6. All inbd VIP Code 7 or higher, pax, cargo acft must ctc Palmetto OPS no later than 30 min prior to ldg. AMC acft ops rstd dur Bird Watch cond moderate (tkf or ldg permission only when departing/arr tce avoid identification bird act, no lcl IFR/VFR tfc pat acft) and severe (tkf and ldg prohibited without OG/CC apvl), ctc Palmetto Ops for current Bird Watch cond. Non-AMC aircrews req RON svc ctc Comd Post (Palmetto OPS) DSN 673-8400, C843-963-8400 prior arr. Terminal apron rstd to coml air carrier and acft for cstmns clnc by PPR. C5, B747, and AN-124 acft taxi with outboard engine at idle. Exp **Rwy 15-33** ops suspended 1230-1300Z daily for A-G inspection. **CAUTION** **Rwy 15-33** 1000' overruns has frangible raised apch lgt. **Rwy 15-33** raised apch lgt in ovrn, **Rwy 03-21** ovrn 800'. Fuel pit/switch obst 36" high lctd 75' left of Twy D cntrln lght of Twy E. **Rwy 21** frequently parked train cars (25' AGL), const/utility storage yard (20 AGL) 1000' from thld and grvl piles (50' AGL) 1500' from thld. Mil side wing tip clnc lines. **Twy D** 161' from twy cntrln and ramp int twy 115' from cntrln. **Rwy 15-33** 1' raised thld lgt. **Rwy 15-33** 1000' ovrn has frangible raised apch lgt. **Twy D** and mil ramp uncltd movement area. Reduced ARFF capability for C-5 and AN-124 acft, degradation of fire fighting capability. C-5/AN-124 with emerg must closely coord rqr with Palmetto Ops. Mil ramp acft ctc CHS GND for engine start and taxi. **Rwy Cond Code** (RwyCC) not rptd. Afld grass cutting ops conducted in ctl movement area year round; ctc Afld Mgmt for daily location. **TFC PAT** TPA—Rectangular 1154' AGL/1200' MSL, overhead 1654' AGL/1700' MSL, lgt acft 654' AGL/700' MSL, C5A 1954' AGL/2000' MSL. **MISC** Tmptry storage of classified materials: Ltd classified storage avbl. 24 hr prior notice rqr with Afld Mgmt. Prior coord rqr. Ctc Base Ops 24 prior to arr. No classified stor at Comd Post. For Top Secret storage ctc 437 SOS 24 hrs prior to ARR DSN 673-0955, C843-963-0955. Afld Mgmt out of office ctc nr C843-609-4362. If civ side of arpt is final destination, acft commander will so indicate on DD 175. Dangerous cargo acft ctc PTD prim, Palmetto ops when within RDO rng. Pax terminal opr 0930-0330Z daily. After hrs ctc DSN 673-7005/7006 or C843-963-7005/7006. C-17 eng running onloads/offloads avbl 24 hr PN req. Ctc 437 APS DSN 673-3193/4, C843-963-3193/4 for coord/apvl. Pass pax/cargo info to Palmetto OPS 3 hrs prior to arr. Dangerous cargo acft ctc PTD primary, Palmetto OPS secondary. All AMC msn acft ctc Palmetto OPS when within radio range. RVR avbl via FAA twr. Afld sfc wx obsns taken in accordance with FAA criteria, not Air Force criteria. PMSV RDO unavbl. PMSV/phone patch avbl thru 628 CP DSN 673-8400 C843-963-8400. Wx flt closed wkends, hol and down days. Mil wx fld afld support avbl 24/7 for svr wx, C843-754-1956. Msn wx support hrs 1100-2300Z Mon-Thu and 1100-2100Z Fri, DSN 673-3016/3644, C843-963-3016, clsd wkend, hol, and down days. Msn wx support brfgs for aircrew avbl via the 260WS/Barksdale AFB DSN 331-2651/C318-529-2651 dur mil wx flt closure hrs. Combat off-load ops on N end of Twy D must ensure that pallets land prior to lead-in line to **Rwy 15** apch end; ctc GND if pallet lands by lead-in line. **Rwy 15-33** and **03-21** grooved.

CONTINUED ON NEXT PAGE

**CONTINUED FROM PRECEDING PAGE**

**AIRPORT MANAGER:** 843-761-7000  
**WEATHER DATA SOURCES:** ASOS 124.75 (843) 554-9862. LLWAS. WSP.  
**COMMUNICATIONS:** D-ATIS 124.75 UNICOM 122.95 PTD 372.2  
 RCO 122.2 (ANDERSON RADIO)  
 RCO 122.1R 113.5T (ANDERSON RADIO)  
 (R) **APP CON** 120.7 306.925 (151°-330°) 121.275 379.925 (331°-150°) 284.0 317.45  
 (R) **DEP CON** 120.7 306.925 (151°-330°) 121.275 379.925 (331°-150°)  
**TOWER** 126.0 **GND CON** 121.9 **CLNC DEL** 127.325 291.65  
**PALMETTO OPS** 134.1 349.4 (Have quick timing avbl 255.5)  
**CPDLC** (LOGON KUSA)  
**PDC**

**AIRSPACE:** CLASS C svc ctc **APP CON.**  
**RADIO AIDS TO NAVIGATION:** NOTAM FILE CHS.  
**(VH) (H) VORTAC** 113.5 CHS Chan 82 N32°53.66' W80°02.27' at fld. 39/5W.  
 VOR unusable:  
 070°-106° byd 40 NM  
 106°-116°  
 116°-146° byd 40 NM  
 248°-272° byd 40 NM blo 8,000'  
**TACAN AZIMUTH** unusable:  
 109°-120° byd 25 NM  
 137°-147°  
 160°-170°  
 229°-262° byd 12 NM blo 5,000'  
 262°-272° byd 15 NM blo 5,000'  
**ASHLY NDB (HW/LOM)** 329 CH N32°58.58' W80°05.85' 155° 5.5 NM to fld. 36/7W.  
**ILS** 109.7 I-CHS Rwy 15. Class IIE. LOM ASHLY NDB.  
**ILS** 108.9 I-CCI Rwy 33. Class ID. ILS/localizer unusable byd 20° right of course.

**CHARLESTON EXEC** (JZI)(KJZI) 6 SW UTC-5(-4DT) N32°42.06' W80°00.20'

**CHARLOTTE**  
**H-9C, 12G, L-24I**  
**IAP**

19 B NOTAM FILE AND  
**RWY 09-27:** H5350X100 (CONC-GRVD) S-60, D-100 HIRL  
**RWY 09:** REIL. PAPI(P4L)—GA 3.0° TCH 50'. Trees.  
**RWY 27:** REIL. PAPI(P4R)—GA 3.0° TCH 44'. Thld dspcld 350'.  
 Brush.  
**RWY 04-22:** H4313X150 (CONC) S-45, D-56 MIRL  
**RWY 04:** Tree.  
**SERVICE:** S2 **FUEL** 100LL, JET A **LGT** SR-SS, to actvt and incr intst  
 REIL Rwy 09 and 27; HIRL Rwy 09-27; MIRL Rwy 04-22—CTAF.  
 SR-SS, PAPI Rwy 09 and 27 opr consly. SS-SR, REIL Rwy 09 and 27;  
 PAPI Rwy 09 and 27; HIRL Rwy 09-27 opr consly, to incr intst—CTAF.  
 SS-SR, to actvt MIRL Rwy 04-22—CTAF. Supplementary lgt'd  
 windcones Rwys 04, 22, 09 and 27.

**AIRPORT REMARKS:** Attended 1100-0300Z. Deer and birds on and invof  
 arpt.

**AIRPORT MANAGER:** 843-767-7000  
**WEATHER DATA SOURCES:** AWOS-3 123.775 (843) 559-3123.  
**COMMUNICATIONS:** CTAF/UNICOM 122.8

(R) **APP/DEP CON** 120.7  
**CLNC DEL** 119.85

**CLEARANCE DELIVERY PHONE:** For CD ctc Charleston Apch at 843-414-2832.

**RADIO AIDS TO NAVIGATION:** NOTAM FILE CHS.  
**(VH) (H) VORTAC** 113.5 CHS Chan 82 N32°53.66' W80°02.27' 176° 11.7 NM to fld. 39/5W.  
 VOR unusable:  
 070°-106° byd 40 NM  
 106°-116°  
 116°-146° byd 40 NM  
 248°-272° byd 40 NM blo 8,000'  
**TACAN AZIMUTH** unusable:  
 109°-120° byd 25 NM  
 137°-147°  
 160°-170°  
 229°-262° byd 12 NM blo 5,000'  
 262°-272° byd 15 NM blo 5,000'  
**ILS/DME** 110.7 I-ETI Chan 44 Rwy 09.

