

NEW CUYAMA (L88) 0 S UTC-8(-7DT) N34°56.41' W119°41.17'

LOS ANGELES

2204 NOTAM FILE RIU

L-3D, 7A

RWY 11-29: H3380X60 (ASPH) 1.5% up E

RWY 11: Rgt ttc.

AIRPORT REMARKS: Unattended. Acft parking 125 ft north of rwy centerline at Rwy 11 apch end. Rwy 11 +25 ft power poles and p-lines run partially underground 270 ft from rwy end, 164 ft right of centerline.

AIRPORT MANAGER: 805-770-0926

COMMUNICATIONS: CTAF 122.9


CLEARANCE DELIVERY PHONE: For CD ctc Los Angeles ARTCC at 661-575-2079.

RADIO AIDS TO NAVIGATION: NOTAM FILE RIU.

FELLOWS (VL) (L) VOR/DME 117.5 FLW Chan 122 N35°05.59' W119°51.93' 120° 12.7 NM to fld. 3870/16E.

VOR unusable:

029°-040° byd 40 NM
 030°-070° byd 25 NM blo 8,500'
 050°-059° byd 40 NM
 060°-070° byd 40 NM blo 10,000'
 060°-070° byd 49 NM
 072°-088° byd 40 NM blo 12,500'
 072°-088° byd 55 NM
 094°-120° byd 40 NM
 133°-210° byd 40 NM
 145°-215° byd 25 NM blo 9,500'
 215°-219° byd 40 NM
 356°-360° byd 40 NM



NEW JERUSALEM (See TRACY on page 294)

NORMAN Y MINETA SAN JOSE INTL (See SAN JOSE on page 273)

NORTH ISLAND NAS (HALSEY FLD) (NZY)(KNZY) NAS (ARNG) 3 SW UTC-8(-7DT) N32°41.89'

LOS ANGELES

W117°12.79'

26 B NOTAM FILE NZY Not insp.

RWY 18-36: H8001X200 (PEM) PCN 59 R/B/W/T HIRL

RWY 18: REIL. PAPI(P4L)—GA 3.0° TCH 49'.

RWY 36: SALSF. REIL. PAPI(P4L)—GA 3.0° TCH 47'.

RWY 11-29: H7501X200 (PEM) PCN 59 R/B/W/T HIRL

RWY 29: ALSF1. REIL. PAPI(P4L)—GA 3.0° TCH 46'.

ARRESTING GEAR/SYSTEM

RWY 18 HOOK E28(B) (1850')

HOOK E28(B) (1701') **RWY 36**

RWY 11 HOOK E28(B) (1500')

HOOK E28(B) (2601') **RWY 29**

SERVICE: **MILITARY— A-GEAR** Short-fld A-Gear Rwy 36 nmly de-rigged. Long-fld A-Gear Rwy 36 nml de-rigged. Short-fld A-Gear 29 de-rigged. Long-fld a-gear Rwy 29 nmly rigged. **JASU** 2(GTC-85) 2(NC-8) **FUEL** Exp refuel delays. 100LL, J5. **FLUID SP PRESAIR. OIL** O-128-148-156-Rstd oil analysis avbl, prior coord rqr. **TRAN ALERT** Opr 1400-0600Z± wkd and 1600-0600Z± weekend; (DT- 1300-0500Z± weekend and 1500-0500Z± weekend). No tran maint/ltd svc. Tran aircrew must remain with acft to provide technical drct/assistance in svcg. Air trml/tran line coord all refuel req. Arr acft passenger svc req to lineman. All tran pilots ck in with ODO, Base OPS Bldg 516, upon arr. LOX not avbl.

NOISE: Strict compliance rqr.

CONTINUED ON NEXT PAGE

CONTINUED FROM PRECEDING PAGE

MILITARY REMARKS: Opr Mon 1430Z†–Sat 0600Z†, Sat 1600Z†–Sun 0600Z†, Sun 1600Z†–Mon 0600Z†. Ctc amgr 619-545-8243/619-778-2074 for info concerning civil acft ldg pmts. CLOSED 0200Z† day prior to 1430Z† day following all Federal hol. Airfield firefighting capability CAT-2. See FLIP AP/1 Supplementary Airport Remarks. **RSTD** Call ODO Btn 1300Z-0500Z† wkdays DSN 735-8233, C619-545-8233 for PPR. Lcl flt drg RON prohibited. MV-22, CMV-22, F-35B acft VTOL ops from any rwy, twy or helipad are prohibited, exc when an emerg situation dictates. CMV-22 VTOL ops (FCF) auth on Twy Echo between Twy Charlie and Helipad 12. **CAUTION** Extv VFR helicopter opr sfc-500' vcnty of arpt and sfc-2000' 8 NM SE. Lgt civ acft climb/descent thru Rwy 29 final apch course byd 6 DME enter/dep San Diego Class B Airspace VFR corridor. Avoid cntrln lgt dur Rwy 29 or Rwy 36 arrestment to prevent tailhook bounce. Rwy 18-36 rwy distance markers less than the required 50' off the rwy edge. Twy L edge lghts not within 10' of marked twy edge. Heavy vehicle tfc cross Twy L and A. Bird haz May-Oct, particularly at dep end Rwy 29. Rwy 11-29 sfc area btn the rwy edge lines and rwy edge lghts, aprx 50' on either side, is cracked and has loose gvl. Rwy 11-29 edge lghts lctd 50' outboard of rwy edge lines, and are not within 10' of the marked rwy edge. Pilots should exercise caution transiting the area btn the rwy edge lines and rwy edge lghts. Dist btn Twy B1 cntrln and Twy B2 cntrln is 200 ft which is 37.5 ft short of the rqrd 237.5 ft. No twy lghts on Twy H and Twy D. **TFC PAT** Use max exterior lgt blo 10,000' within 10 NM. All tran acft ltd to full stop only. Touch-and-go/low apch not avbl. Tran acft section apch not authorized. Reduced rwy separation std in effect USN/USMC acft. **CSTMS/AG/IMG** Cstms avbl with 2 hr ntc Mon-Sat 1600-0100Z†. Minimum 4 hr ntc rqr 0100-1600Z†. **MISC** VIP/logistic flts ctc Base OPS prior to ldg. Tsnt pilot with DV 6 or higher ctc baseops on 355.5 to update ETA when practical. **ARNG** Army Base OPS DSN 735-0101, C619-545-0101.

COMMUNICATIONS: ATIS 317.8 (1430Z† Mon-0600Z† Sat, 1600Z† Sat-0600Z† Sun, 1600Z† Sun-0600Z† Mon. Clsd 0200Z† day prior to 1430Z† day following all Federal hol)

® **SOCAL APP/DEP CON** 125.15 317.55 (Radar advsy and sequencing to arpt avbl VFR arr on req)

NAVY NORTH ISLAND TOWER 135.1 336.4 340.2 (1430Z† Mon-0600Z† Sat, 1600Z† Sat-0600Z† Sun, 1600Z† Sun-0600Z† Mon. Clsd 0200Z† day prior to 1430Z† day following all Federal hol)

GND CON 118.0 360.675 **CLNC DEL** 128.4 288.25 **PMSV METRO** 342.35 **BASE OPS** 355.5

CLEARANCE DELIVERY PHONE: For CD when ATCT clsd ctc SoCal Apch at 800-448-3724.

AIRSPACE: CLASS D svc 1430Z† Mon-0600Z† Sat, 1600Z† Sat-0600Z† Sun, 1600Z† Sun-0600Z† Mon, clsd from 0200Z† day prior to 1430Z† day following all fed hol; other times CLASS G.

VOR TEST FACILITY (VOT) 109.0

RADIO AIDS TO NAVIGATION: NOTAM FILE NZY.

(L) **TACAN** Chan 117 NZY (117.0) N32°42.16' W117°12.97' at fld. 17/11E.

No NOTAM MP: 1500-1700Z† Sun

TACAN AZIMUTH unusable:

183°-232° byd 20 NM blo 3,000'

233°-303° byd 15 NM blo 3,000'

304°-343° byd 30 NM blo 3,000'

DME unusable:

183°-232° byd 20 NM blo 3,000'

233°-303° byd 15 NM blo 3,000'

304°-343° byd 30 NM blo 3,000'

ASR/PAR

COMM/NAV/WEATHER REMARKS: Radar see Terminal FLIP for Radar Minima.