

MONTGOMERY—GIBBS EXEC (MYF)(KMYF) 6 N UTC-8(-7DT) N32°48.94' W117°08.37'

LOS ANGELES

427 B TPA—See Remarks NOTAM FILE MYF

L-4H

RWY 10L-28R: H4598X150 (ASPH-RFSC) S-12 PCN 48 F/C/Y/T

IAP, AD

MIRL 0.3% up E

RWY 10L: PAPI(P4L)—GA 3.4° TCH 45'.

RWY 28R: MALSR. PAPI(P4R)—GA 3.0° TCH 41'. Thld dsplcd 1199'. Rgt tfc.

RWY 10R-28L: H3401X60 (ASPH-RFSC) S-12 PCN 44 F/C/Y/T

RWY 10R: Rgt tfc.

RWY 28L: REIL.

RWY 05-23: H3400X75 (ASPH-TRTD-RFSC) S-12 PCN 37 F/B/Y/T 0.3% up NE

RWY 05: Thld dsplcd 390'.

SERVICE: S4 FUEL 100LL, JET A, A+, UL94 OX 1, 4 LGT When twr clsd ACTIVATE PAPI Rwy 10L and 28R, MALSR Rwy 28R—CTAF, MIRL Rwy 10L-28R opr continuously.

NOISE: For noise abatement regulations ctc the noise abatement office at 858-573-1436. Act with high noise levels are requested to use Rwy 10L-28R. Extreme noise sensitive areas west and south of arpt. Noise monitoring in effect. Maximum noise limit 0730-1430Z‡ 70 DB over residential areas. Maximum noise limit 1430-0730Z‡ 88 DB.

AIRPORT REMARKS: Attended Mon-Sat 1500-0200Z‡. Be alert heavy act activity in the vicinity of Lake Murray and Mt Soledad. Pilots are urged to be vigilant for other act in these areas and to ctc the twr early enough for timely tfc advisories if proceeding east bound advise twr of destination arpt. Be alert to military jet act invof arpt and 4.7 NM NW of arpt bearing 312° invof Mission Bay VORTAC. Be alert birds on and in the vicinity of arpt. Coyote activity on rwys and twys. Practice low approaches are prohibited 0730-1430Z‡. Simulated engine failures are prohibited over residential areas. No jet touch and go opns. Dep use Rwy 10L when tower not opr and wind permitting. TPA—Rwy 10R-28L, 10L-28R and 05-23—multi-engine/turbo powered 2027(1600); Single eng 1427(1000). No act over 20,000 lbs on Twy J rstd by FBO. TxI E non-std, act with wingspan greater than 35.5 ft use caution. Twy K rstd to wingspan no greater than 58'. Ldg fees for ops by non-based Part 91 and Part 135 certified act. See Special Notice—Montgomery Gibbs Executive Airport "Soledad" VFR Procedure, See Special Notices—Arrival Alert..

AIRPORT MANAGER: 858-573-1430

WEATHER DATA SOURCES: ASOS 126.9 (858) 576-4337.

COMMUNICATIONS: CTAF 119.2 ATIS 126.9 858-277-3075 UNICOM 123.075

RCO 122.2 (SAN DIEGO RADIO)

Ⓡ SOCIAL APP CON 124.35

Ⓡ SOCIAL DEP CON 119.6

TOWER 119.2 (All rwys, except Rwy 28R btw 1800-0200Z‡) 125.7 (Rwy 28R btw 1800-0200Z‡) GND CON 118.225

CLNC DEL 123.725

CLEARANCE DELIVERY PHONE: For CD when ATCT clsd ctc SoCal Apch at 800-448-3724.

AIRSPACE: CLASS D svc 1400-0500Z‡; other times CLASS G.

VOR TEST FACILITY (VOT) 109.0



CONTINUED ON NEXT PAGE

CONTINUED FROM PRECEDING PAGE

RADIO AIDS TO NAVIGATION: NOTAM FILE SAN.

MISSION BAY (VH) (H) VORTACW 117.8 MZB Chan 125 N32°46.93' W117°13.53' 050° 4.8 NM to fld. 10/15E.

VOR unusable:

- 026°-088° byd 40 NM
- 090°-100° byd 28 NM
- 100°-130° byd 17 NM
- 130°-190° byd 14 NM
- 190°-219° byd 20 NM
- 215°-241° byd 40 NM
- 242°-252° byd 40 NM blo 8,000'
- 242°-252° byd 55 NM blo 18,000'
- 253°-288° byd 40 NM
- 289°-299° byd 40 NM blo 4,500'
- 289°-299° byd 49 NM
- 300°-333° byd 40 NM
- 308°-350° byd 20 NM blo 8,000'
- 347°-351° byd 40 NM
- 352°-002° byd 40 NM blo 7,000'
- 352°-002° byd 52 NM

TACAN AZIMUTH unusable:

- 310°-350° byd 15 NM blo 6,000'
- 310°-350° byd 30 NM blo 10,000'

DME unusable:

- 310°-350° byd 20 NM blo 6,000'
- 310°-350° byd 30 NM blo 10,000'

ILS/DME 111.95 I-MYF Chan 56(Y) Rwy 28R. Class IT. LOC/DME unmonitored when ATCT closed.

COMM/NAV/WEATHER REMARKS: Freq 125.7 also used for touch and go landings Rwy 10L-28R.

HELIPAD H1: H48X48 (ASPH)

SAN DIEGO INTL (SAN)(KSAN) P (CG) 2 W UTC-8(-7DT) N32°44.01' W117°11.38'

LOS ANGELES

17 B AOE Class I, ARFF Index D NOTAM FILE SAN

H-41, L-4H

RWY 09-27: H9401X200 (ASPH-CONC-GRVD) S-120, D-250, 2D-550, 2D/2D2-1120 PCR 851 F/A/X/T

IAP, AD

HIRL CL

RWY 09: MALSR. TDZL. PAPI(P4L)—GA 3.3° TCH 76'. RVR-TR Thld dsplcd 1000'. Tree.

RWY 27: MALS. TDZL. PAPI(P4R)—GA 3.5° TCH 66'. RVR-TR Thld dsplcd 1810'. Sign. Rgt tfc.

RUNWAY DECLARED DISTANCE INFORMATION

RWY 09: TORA-8280 TODA-9401 ASDA-8280 LDA-7280

RWY 27: TORA-9401 TODA-9401 ASDA-9401 LDA-7591

ARRESTING GEAR/SYSTEM

RWY 27: EMAS

SERVICE: S2 FUEL 100LL, JET A OX 1, 2 LGT Twy C edge lgts OTS indef. Rwy 27 PAPI unusable byd 5° left and right of centerline. MILITARY— A-GEAR Rwy 27 EMAS 315' x 218'. FUEL (NC-100LL, A) FLUID OX.

NOISE: Dep curfew in efct. Deps prohibited 0730-1430Z†. Sgfrnt fines. Med fits exempt with form. Noise ofc 619-400-2660. NOTE: See Special Notices—Aircraft Noise Prohibitions/Restrictions.

CONTINUED ON NEXT PAGE