LOC/DME I-IND	APP CRS	Rwy Idg 11200
111.75	050°	TDZE 747
Chan 54 (Y)		Apt Elev 796

ILS or LOC RWY 5L

INDIANAPOLIS INTL (IND)

T A Simultaneous approach authorized. DME or RADAR required. For inop ALS, increase S-LOC 5L Cat C/D visibility to 1⅜ SM. OSCRR fix minimums: For inop ALS, increase S-LOC 5L Cat C/D visibility to RVR 5500.

ALSF-2

MISSED APPROACH: Climb to 1700 then climbing left turn to 3000 direct VHP VORTAC then on VHP VORTAC R-303 to KEADY/VHP 4.9 DME/RADAR and hold.

D-ATIS	INDIANAPOLIS APP CON	INDY TOWER	GND CON	CLNC DEL	CPDLC
134.25	128.175 317.8	120.9 251.1	121.9	128.75 251.1	



VGSI and ILS glidepath not coincident (VGSI Angle 3.00/TCH 74).

1700 3000 VHP VHP R-303 KEADY VHP 4.9 RADAR



CATEGORY	A	B	C	D
S-ILS 5L		947/18	200 (200-½)	
S-LOC 5L	1220/24	473 (500-½)	1220/50	473 (500-1)
C CIRCLING	1420-1	624 (700-1)	1420-1¾ 624 (700-1¾)	1560-2½ 764 (800-2½)
OSCRR FIX MINIMUMS (DUAL VOR RECEIVERS or DME REQUIRED)				
S-LOC 5L	1120/24	373 (400-½)	1120/35	373 (400-⅝)
C CIRCLING	1420-1	624 (700-1)	1420-1¾ 624 (700-1¾)	1560-2½ 764 (800-2½)

ELEV 796 D TDZE 747



HIRL all Rwys
TDZ/CL Rwys 5L and 5R

FAF to MAP 4.1 NM

Knots	60	90	120	150	180
Min:Sec	4:06	2:44	2:03	1:38	1:22

EC-2, 26 DEC 2024 to 23 JAN 2025
EC-2, 26 DEC 2024 to 23 JAN 2025